

Development of Cu-Nb composite superconducting cavities for enhanced operational stability at IMP

Shichun Huang, Long Peng, Xiangchen Gu et al.

Linac Center, Institute of Modern Physics, CAS

August 20, 2026

1. Introduction

2. Cu-Nb composite cavities based on **Cu-Nb composite sheet**


3. Cu-Nb composite cavities based on **electroforming copper**

- Sample studies
- Cu-Nb composite prototype cavity
- HWR040 Cu-Nb composite cavity for engineering application


4. Conclusions and plans

❑ Operation experience of the Chinese ADS Front-end Demo Linac(CAFe)

- 43% of machine trips originated from SRF system



Layout of CAFe




Machine failure analysis
[Y. He, SRF2019]

❑ Factors constrain the operational stability of the low-beta SRF cavities

- **Thermal stability:** thermal breakdown due to defects, field emission and multipacting electrons etc.
- **Mechanical stability:** helium pressure fluctuation detuning(df/dp), Lorentz force detuning(LFD) , environmental vibration etc.


□ Cu-Nb composite cavity: thin-walled Nb cavity backed up with thick copper shell

- **Higher thermal stability**
 - Nb thermal conductivity~ 60 W/(m*K) at 4.2 K
 - Cu thermal conductivity 400 W/(m*K) even more
- **High mechanical stability** (df/dp , LFD, environment vibration etc.)
- **RF performance guaranteed**- high gradient recipes developed for the bulk Nb cavity
- **Low niobium cost**(3 mm to 1.5 mm or less)




1.3 GHz single-cell Cu-Nb composite cavity made of Cu-Nb composite sheets

- Cu (6.8mm) and Nb (1.5mm)
- Cu-Nb composite sheets preparation by **Hot isostatic pressure**
- surface treatment: **BCP and 600 °C /10 h**




Test results

- RF performance: **comparable to Nb cavity with similar surface treatment(BCP)**
- Mechanical property(remarkable improvement)
 - ✓ df/dp : -17 (Cu-Nb) vs. ~ -106 (Nb) Hz/mbar
 - ✓ $LFD\ coeff.$: ~ -0.3 (Cu-Nb) vs. ~ -1.7 (Nb) Hz(MV/m)⁻²




RF performance at in different cooling




Comparison of LFD coeff. between Cu-Nb composite cavities and Nb cavity(3mm)


- **Cooling dynamics** significantly impacts the magnetic flux generation and trapping
- **R_s** exhibits saturations at a lower cooling rate
- **Quench related Q_0 degradation** tends to saturate after several quench events



B field at the equator during different cooling



Q_0 and R_s Vs. cooling rate
[$E_{pk} = 10$ MV/m , 2 K]




Quenches related Q_0 degradation
[$E_{pk} = 50$ MV/m , 2 K]

❑ **Fabrication difficulties of complex superconducting cavities using Cu-Nb composite sheets**

□ Manufacturing procedures of the Cu/Nb composite cavity by electroplating copper technology


1. Bulk Nb cavity fabrication
2. Electroplating a buffer layer and a copper layer, sequentially on the outer surface of the bulk niobium cavity
3. Heat treatment: **850 °C /70 mins**, to enhance the bonding strength and minimize the thermal resistance between the Nb and Cu layer
4. Electroplate the thick copper layer (e.g. 5 mm).




Challenges

- Strong bonding between copper and niobium layer
- High copper thermal conductivity
- Suitable for high-temperature heat treatment

Study the thermal and mechanical properties of Cu-Nb composite samples




➤ Mechanical properties: tensile strength and shear strength



Mechanical properties of heat-treated samples


- Heat treatment(HT) may degrade mechanical properties
- Hot isostatic pressure(HIP) treatment enhance mechanical properties.



Mechanical properties of HIP treated samples

❑ Thermal properties: direct current and pulse plating(PP) copper



- Residual Resistivity Ratio(RRR) and thermal conductivity of Cu



- $RRR > 100$
- $K_{Cu} > 1000 \text{ W/(m·K)}$, [$\kappa_{DC} = 1378$, $\kappa_{PP} = 1451$] @ 4 K
- RRR and K is superior to that of oxygen-free copper


- Cu-Nb interface thermal resistance

- Hot isostatic pressure treatment substantially decrease Cu-Nb thermal resistance, ~75.2% decrease
- All the data was used for Cu-Nb cavity design




□ HWR010 Cu-Nb composite cavity design: aimed to improve the stability of low-beta cavity

- Local area helium cooling -inner conductor and short plates
- Pipes and conduction cooling- outer conductor




Temperature distribution at E_{pk} of 26 MV/m
Delta T max= 0.05 K



HWR010 bulk niobium cavity

$$\begin{aligned} df/dp &= 7 \text{ Hz/mbar} \\ df/dp &= -0.6 \text{ Hz/mbar} \end{aligned}$$

$$\begin{aligned} \text{LFD coef.} &= -5.1 \text{ Hz/(MV/m)}^2 \\ \text{LFD coef.} &= -1.7 \text{ Hz/(MV/m)}^2 \end{aligned}$$



Cooling configuration of the HWR010 Cu-Nb cavity

□ Fabrication procedures


1) Nb cavities fabrication



2) Vacuum heat treatment of Nb-Ag-Cu layers



3) First 2 mm copper layer plating by pulse power supply



4) Last 3mm copper layer plating by DC power supply



5) Machining after electroplating copper



6) The finished HWR010 Cu-Nb cavity




- **Surface treatment:** BCP~150 um and 600 °C/10 h furnace outgassing before electroplating copper
- Cavity was sealed and filled with high-purity water during electroplating process

❑ Cryogenic test results- vertical test

- **Surface treatment:** 30 μm BCP, 380°C/2.5 h heat treatment for stress relief of copper, 30 μm BCP
- **Slow cooling** at T_c crossing of niobium adopted, B field < 10 mG
- **RF performance:** $E_{pk_av.} = 40 \text{ MV/m}$, limited by field-emission induced thermal breakdown




HWR010 Cu/Nb cavity mounted
on vertical test stand




Q_0 vs. E_{pk} at 4.2 K

❑ Cryogenic test results- horizontal test

- ✓ 9 HWR010 Cu-Nb cavities in string
- ✓ Average $E_{pk} \sim 35.3$ MV/m, limited by FE
- ✓ $Q_0 = 4.31E8 @ E_{pk} = 20$ MV/m at 4.2 K
- ✓ Mechanical performance: df/dp and LFD_coeff. improved 85% and 50%




X-Ray vs. E_{pk}



df/dp



The assembled 9 HWR010 Cu/Nb cavities string




LFD_coeff.

❑ 60 HWR040 Nb cavities are used in CiADS Linac, one cryomodule will be replaced by Cu-Nb cavities for the verification of Cu-Nb composite cavity technology on-line


✓ **HWR040 Cu-Nb composite cavity design**

- Local area helium cooling - inner conductor and short plates
- Conduction cooling - outer conductor



Final HWR040 model(left) and cutaway view(right)

- ✓ Two Nb cavities has been fabricated
- ✓ Buffer layer with thin Ag and Cu layer were plated
- ✓ The cavity will be ready for test in October



Bulk niobium cavity



Cavities with buffer layer

❑ 1.3 GHz single-cell Cu-Nb composite cavity made of Cu-Nb composite sheets

- Verify the enhanced mechanical properties of Cu-Nb composite cavity
- Slowing cooling crossing T_c is preferred for obtaining high-performance of the copper-niobium composite
- Quench related Q_0 degradation tends to saturate after several quench events

❑ Cu-Nb composite cavities based on electroforming copper technology have been explored

❑ HWR040 Cu-Nb composite cavities will be ready for vertical test in October, and proton beam acceleration next year

Thanks for your attentions!