



Contribution ID: 1882 Contribution code: WEPA031

Type: **Poster Presentation**

## Beam dynamics study of the high-power electron beam irradiator using niobium-tin superconducting cavity

*Wednesday, 10 May 2023 16:30 (2 hours)*

At KEK a design of the compact 10 MeV, 50 mA accelerator for irradiation purpose was proposed. Current design includes a 100 kV thermionic DC electron gun with an RF grid, 1-cell normal-conducting buncher cavity, and Nb3Sn superconducting cavities to accelerate the beam to the final energy of 10 MeV. The goal of the present beam dynamics study is the beam loss suppression (to the ppm level), since it results in a thermal load on the cavity. Then the beam performance at the accelerator exit should be confirmed. The main issue was to transport the beam without loss, since the initial electron energy (100 keV) is low, and the beam parameters are intricately correlated. In addition, the space charge effect is considerable. For this reason, simultaneous optimization of multiple parameters was necessary. Here we report optimization results and their effect on the design of the machine.

### Funding Agency

### Footnotes

### I have read and accept the Privacy Policy Statement

Yes

**Primary author:** TANAKA, Olga (High Energy Accelerator Research Organization)

**Co-authors:** YAMAMOTO, Masahiro (High Energy Accelerator Research Organization); Dr HONDA, Yosuke (High Energy Accelerator Research Organization); SAKAI, Hiroshi (High Energy Accelerator Research Organization); YAMADA, Tomohiro (High Energy Accelerator Research Organization)

**Presenter:** Dr HONDA, Yosuke (High Energy Accelerator Research Organization)

**Session Classification:** Wednesday Poster Session

**Track Classification:** MC5: Beam Dynamics and EM Fields: MC5.D08: High Intensity in Linear Accelerators Space Charge, Halos