



Contribution ID: 1047 Contribution code: TUPS75

Type: **Poster Presentation**

Machine learning based response matrix correction

Tuesday, 21 May 2024 16:00 (2 hours)

The response matrix is the closed orbit distortion at each BPM responses to the change in every corrector. For a large ring, the response matrix has tens of thousands of data points which can fully include the linear optics of the ring. LOCO use response matrix for lattice calibration and error correction. For 4th generation diffraction limitation ring which uses many strong sextupoles and octupoles, the response matrix will influence by the nonlinearity and can only be driven from closed orbit distortion tracking not from linear matrix. The strong nonlinearity will make it difficult for LOCO to match lattice parameters and also need more time to get Jacobi matrix. Machine learning may help bypass the time assuming Jacobi matrix and avoid local optima. This work try to improve the speed and accuracy of LOCO by machine learning method.

Footnotes

Funding Agency

Paper preparation format

LaTeX

Region represented

Asia

Primary authors: CHEN, Liwei (Tsinghua University); Mr TANG, Jiazhen (Tsinghua University in Beijing)

Co-author: TANG, Chuanxiang (Tsinghua University in Beijing)

Presenter: Mr TANG, Jiazhen (Tsinghua University in Beijing)

Session Classification: Tuesday Poster Session

Track Classification: MC6: Beam Instrumentation, Controls, Feedback, and Operational Aspects: MC6.D13 Machine Learning