



Contribution ID: 1437 Contribution code: THPS29

Type: Poster Presentation

## Simulation study of nanosecond pulse power based on gyromagnetic nonlinear transmission line

*Thursday, 23 May 2024 16:00 (2 hours)*

On-axis injection mode is planned to use in the Southern Advanced Photon Source (SAPS), which requires high quality to injection pulsed power supply. Gyromagnetic nonlinear transmission line (GNLTL) is introduced as a pulse compressor to meet the needs for pulse width. In this paper, 3-D finite element model is established based on Landau-Lifshitz-Gilbert equation and Maxwell's equations. The influence of geometrical sizes and bias magnetic field to output pulse is analyzed for better design of NLTL. A prototype was built with nanosecond pulse width and sub-nanosecond rise time to verify the simulation.

### Footnotes

### Funding Agency

### Paper preparation format

Word

### Region represented

Asia

**Primary author:** ZHANG, Wenbin (Institute of High Energy Physics)

**Co-authors:** QI, Xin (Chinese Academy of Sciences); LIN, Munan (Chinese Academy of Sciences); LI, Hai (Dongguan Neutron Science Center)

**Presenter:** ZHANG, Wenbin (Institute of High Energy Physics)

**Session Classification:** Thursday Poster Session

**Track Classification:** MC7: Accelerator Technology and Sustainability: MC7.T16 Pulsed Power Technology