



Contribution ID: 2123 Contribution code: SUPG051

Type: Student Poster Presentation

## Multi-mode cavity design and characterization

*Sunday, 19 May 2024 14:00 (4 hours)*

We present the design and initial characterization of a multi-mode cavity, a novel electromagnetic structure with potential benefits such as compactness, efficiency, and cost reduction. The 2nd Harmonic mode was chosen to linearize the fundamental mode for use as an accelerating and bunching cavity. The reduction in the number of cavities required to bunch and accelerate promises cost and space savings over conventional approaches. Superfish and COMSOL simulations were used to optimize the cavity's geometry with the goal of balancing various design parameters, such as quality factor (Q-factor), harmonic modes, and mode coupling. A 3D-printed copper-plated cavity was used to validate code predictions.

The cavity's multi-mode nature positions it for use with other harmonic modes with small deviations in design. For example, a 3rd Harmonic can be used to decrease energy spread by widening the peak of the fundamental. This research lays the foundation for further exploration of the cavity's applications and optimization for specific use cases, with potential implications for a wide range of accelerator fields.

### Footnotes

### Funding Agency

This work was supported by the U.S. DOE Office of Science, High Energy Physics under Cooperative Agreement Award No. DESC0018362 and Award No. DESC0020429. Dr. Lewellen's work was per

### Paper preparation format

LaTeX

### Region represented

North America

**Primary author:** Mr SIMS, Benjamin (Michigan State University)

**Co-authors:** LEWELLEN, John (Los Alamos National Laboratory); BARYSHEV, Sergey (Michigan State University)

**Presenter:** Mr SIMS, Benjamin (Michigan State University)

**Session Classification:** Student Poster Session

**Track Classification:** MC7: Accelerator Technology and Sustainability: MC7.T06 Room Temperature

RF