



Contribution ID: 2170 Contribution code: SUPC063

Type: **Poster Presentation**

## Performance optimization design of photocathode injector based on multi-objective genetic algorithm

*Sunday, 19 May 2024 16:00 (2 hours)*

Generating beam with nC-level charge is of great significance for particle colliders. In order to achieve lower emittance and length of bunch, based on the photocathode injector, we designed a L-band gun and L-band accelerating tube. However, with many coupled parameters, it is difficult to optimize its performance to the limit when optimizing them separately. Therefore, we employed a multi-objective genetic algorithm for searching in the multi-dimensional parameter space and utilized a deep Gaussian process as a surrogate model to solve the high-dimensional parameter optimization problem. Through optimization, we successfully obtained the normalized transverse emittance of  $3.4 \pi \text{ mm} \cdot \text{mrad}$  and the bunch length of 1.0 mm for a fixed charge of 5 nC. This indicates that our method can effectively improve the performance of the photocathode injector.

### Footnotes

### Funding Agency

### Paper preparation format

Word

### Region represented

Asia

**Primary author:** SUN, Zheng (Institute of High Energy Physics)

**Co-author:** XIN, Tianmu (Institute of High Energy Physics)

**Presenter:** SUN, Zheng (Institute of High Energy Physics)

**Session Classification:** Student Poster Session

**Track Classification:** MC2: Photon Sources and Electron Accelerators: MC2.T12 Beam Injection/Extraction and Transport