



Contribution ID: 2270 Contribution code: SUPG064

Type: **Poster Presentation**

Improvements of longitudinal stability with LLRF optimization at SIRIUS

Sunday, 19 May 2024 16:00 (2 hours)

SIRIUS is a 4th generation synchrotron light source built and operated by the Brazilian Synchrotron Light Laboratory (LNLS). Recently, investigations of noise sources and the storage ring RF plant identification enabled a fine-tuning of the Digital Low-Level Radio Frequency (DLLRF) parameters. This paper presents the main improvements implemented, which include the mitigation of 60Hz noise from the LLRF Front End and the optimization of the control system parameters. Optimizations in the machine were based on an adjusted model of the SIRIUS storage ring RF plant. Tests with the model's parameters showed that the system's stability was strongly dependent on phase shifts introduced by nonlinearities from the high power RF sources. The new parameters significantly improved the control performance, increasing the bandwidth of the system and reducing longitudinal oscillations. BPM (Beam Position Monitor) and BbB (Bunch-by-Bunch) systems were employed to quantify longitudinal beam stability improvements.

Footnotes

Funding Agency

Paper preparation format

LaTeX

Region represented

North America

Primary author: DAMINELLI, David (Brazilian Synchrotron Light Laboratory)

Co-authors: LIMA, André (Brazilian Synchrotron Light Laboratory); HOSHINO, Felipe Koji Godinho (Brazilian Synchrotron Light Laboratory); SOUZA, Matheus (Estadual de Campinas University); ALVES, Murilo (Brazilian Synchrotron Light Laboratory); FREIRE, Vitor (Centro Nacional de Pesquisa em Energia e Materiais)

Presenter: DAMINELLI, David (Brazilian Synchrotron Light Laboratory)

Session Classification: Student Poster Session

Track Classification: MC6: Beam Instrumentation, Controls, Feedback, and Operational Aspects:
MC6.T27 Low Level RF