

# Overview of accelerating structure research activities at IHEP

*Monday 26 August 2024 16:00 (2 hours)*

In electron linear accelerators, the improvement of the acceleration gradient of the acceleration structure has been a continuous research topic for scientists, which can reduce the construction cost of the entire accelerator by increasing the accelerating gradient. For the CEPC and HEPS projects at IHEP, S-band 3 meters long and C-band 1.8 meters long accelerating structure has been developed. The operating frequencies are 2860 MHz, 2998.8 MHz and 5720MHz respectively. CEPC linac is 30 GeV with S & C-band structures in the TDR phase. The high-power test gradient of S-band accelerating structure reach the 33MV/m. The C-band structures also designed and waiting for high power test. HEPS is 500 MeV linac in-jector and already conditioning for one year. The maximum gradient achieved with the beam during commissioning was approximately 26 MV/m with a beam current of 7 nC. During actual operation, it has been functioning at around 20 MV/m. The electron beam has remained stable up to the present time.

## Footnotes

## Funding Agency

**Primary author:** ZHANG, Jingru (Chinese Academy of Sciences)

**Co-authors:** Dr MENG, Cai (Chinese Academy of Sciences); SHI, Hua (Institute of High Energy Physics); GAN, Nan (Institute of High Energy Physics); XIAO, Ouzheng (Institute of High Energy Physics); LI, Xiaoping (Chinese Academy of Sciences); HE, Xiang (Chinese Academy of Sciences); MA, Xinpeng (Key Laboratory of Particle Acceleration Physics and Technology); LIU, Jindong (Chinese Academy of Sciences); ZHOU, Zusheng (Institute of High Energy Physics); LI, Yuhui (Chinese Academy of Sciences); GAO, Jie (Chinese Academy of Sciences); HE, Da-Yong (Chinese Academy of Sciences); LI, Jingyi (Institute of High Energy Physics)

**Presenter:** ZHANG, Jingru (Chinese Academy of Sciences)

**Session Classification:** Monday Poster Session

**Track Classification:** MC4: Technology: MC4.7 Room temperature RF