

Chromatic index to find a working point for a 4th generation synchrotron light source

Thursday 29 August 2024 16:00 (2 hours)

The design and tuning of a storage ring for a fourth-generation synchrotron light source is very demanding. Recently, some research groups have considered techniques based on quasi-invariants of motion to address this task. This contribution presents tools, based on a quasi-invariant of motion method, for the description and optimisation of the electron dynamics in a storage ring. An overview of this quasi-invariant formalism in the context of electron dynamics in storage rings for synchrotron light sources is presented. Quasi-invariant surface techniques to study and optimise the dynamics of a particular model are shown in detail. The relevance of the distorted chromatic index for cell tuning and for determining a working point of a machine is highlighted. These techniques are implemented to optimise the horizontal electron dynamics generated by a ring model based on a 7BA cell, with 20 cells, 81 pm rad emittance and approximately 490 m circumference, and the results are presented.

Footnotes

Funding Agency

This work was supported by UNAM-PAPIIT IN108522. Proyecto apoyado por el "CONACYT" en el año 2023, con número CF-2023-I-119. E.S. is grateful to CONAHCYT for funding a postdoctoral fellowship.

Primary author: SANCHEZ, Edgar (Universidad Nacional Autónoma de México)

Co-authors: HERNANDEZ, Jorge (Universidad Nacional Autónoma de México); ANTILLÓN, Armando (Universidad Nacional Autónoma de México); FLORES, Alain (Tec de Monterrey); MORENO, Matías (Universidad Nacional Autónoma de México)

Presenter: SANCHEZ, Edgar (Universidad Nacional Autónoma de México)

Session Classification: Thursday Poster Session

Track Classification: MC1: Beam Dynamics, Extreme Beams, Sources and Beam-Related Technologies; MC1.1 Beam Dynamics, beam simulations, beam transport