eeFACT 2025 - 70th ICFA Advanced Beam Dynamics Workshop on High Luminosity Circular e+e-Colliders



Contribution ID: 52

Type: Invited Oral Presentation

The FCC-ee polarimeter

In order to perform the precise energy calibration for the Z and WW modes of the FCC-ee machine, the use of Resonant Depolarization (RDP) method on a set of non-colliding polarized bunches is foreseen. To track the polarization state of these bunches while scanning the depolarization excitation frequency a Compton Polarimeter will be deployed on both colliding beams.

The most recent advances on the Compton Polarimeter design for FCC-ee energy calibration will be presented to the community at the eeFACT conference.

Footnotes

Funding Agency

I have read and accept the Privacy Policy Statement

Yes

Primary authors: Prof. WILKINSON, Guy (Christ church university of Oxford); Dr KEINTZEL, Jacqueline (CERN); Dr MARTENS, Aurelien (Université Paris-Saclay, CNRS/IN2P3, IJCLab); Dr GRANADOS, Eduardo (CERN); Dr KIEFFER, Robert (CERN); Dr LEFEVRE, Thibaut (CERN); Dr MAZZONI, Stefano (CERN)

Presenter: Dr KIEFFER, Robert (CERN)

Session Classification: Polarization, Energy calibration, Monochromatization

Track Classification: WG8 : Polarization, Energy calibration, Monochromatization