

ECRIS 2024 - Proceedings Management

Sunday 15 September 2024 - Thursday 19 September 2024

Welcome Hotel Darmstadt City Center



Book of Abstracts

Contents

Design of a new iron plug for the TRIUMF ECRIS charge state booster	1
Characterization of the 2.45 GHz DREEBIT ECRIS via optical spectroscopy	1
High intensity highly charged ion beams production and operation at IMP	2
Compact 2.45 GHz PMECR ion sources developed for accelerator based radiation therapy facilities at Peking University	2
Intense pulsed uranium ion beams production with ECRISs	3
Characterization of D^+ species in the 2.45 GHz ECRIS for 14-MeV neutron production . .	4
High performance highly-charged ECR ion sources and matching with high-intensity heavy ion accelerator facility	4
Operation with the LAPECR3 ion sources for cancer therapy accelerators	5
An electrostatic ion beam transport system for intense proton source	6
Analysis of beam characteristic variations in the 14.5 GHz ECR ion source at RAON . . .	6
Development of deuterium-deuterium compact neutron source	7
Tests of a low-energy pepperpot based on a micro-channel plate for high current protons sources 4D-emittance characterization	8
RF and multipactor simulations in the plasma chamber of the SILHI proton source	8
Time-resolved measurement of ion beam energy spread variation due to kinetic plasma instabilities in CW and pulsed operation of an ECRIS	9
ALISES II source is still alive	9
Wien Filter upgrade and measurement for BETSI test bench	10
ALISESv3 ion source in various configuration along the year	10
Study of noble gas memory effect of ECR3 at ATLAS	11
Beam intensity prediction using ECR plasma images and machine learning	11
Development of a 100 mA-class CW microwave ion source for industrial accelerators . .	12
Planned optimization of the ion sources on the HIT test bench	13

Performance of the hybrid ECR ion source development at IMP	13
Simulation of Bremsstrahlung emission in ECRIS and its dependence on the magnetic confinement	14
ECR2 performance upgrades at ATLAS	15
Use of a 2.45 GHz ECR ion source for the Neutron Target Demonstrator project	15
Simulation of the Bremsstrahlung emission induced by electrons impinging the plasma chamber walls of the ASTERICS ECRIS	16
Challenges in production of intense metallic ion beams at IMP	17
Characterization of an proton ECR ion source for low beam current	17
Non-intrusive plasma state detection using machine learning	18
Status report on 60 GHz ECRIS activity	19
Development towards intense uranium ion beam production of the RIKEN 28 GHz SC-ECRIS	19
Optical diagnostic studies of the electron cyclotron resonance plasma produced in the GTS-LHC ion source	20
Light ions from the GTS-LHC ion source for future physics at CERN	21
Continuous data-driven control of the GTS-LHC ion source at CERN	21
Operation and development of the 28 GHz electron cyclotron resonance (ECR) ion source at the facility for Rare Isotope Beams (FRIB)	22
A novel design of superconducting magnet for ECR ion source	23
The electrostatic deceleration of ions injected into an ECRIS CB plasma	23
Microwave transmission measurements at the VENUS ECR ion source	24
Efficient injection of high-intensity light ions from an ECR ion source into an RFQ accelerator	24
Role of ECRISs to reveal astrochemical processes	25
ECR ions sources at CRC in UCLouvain, Belgium	26
GANIL cyclotron and ion source for industrial application	26
A novel test-facility for ECRIS plasma diagnostics: optical spectroscopy, X-ray imaging and spectroscopy, mm-wave polarimetry	27
Progress in 3D self-consistent full wave-PIC modelling of space resolved ECR plasma properties	28
A novel inductive oven design for the production of high current, metal ion beams	28
A plasma based, charge state stripper for heavy ion accelerators	29

Applying machine learning techniques to the operation of the superconducting ECR ion source VENUS	30
Transport of intense Bi and U beams into an RFQ	30
Waveguide DC breaks with optimized impedance matching networks	31
GANIL cyclotron ion sources: optimisation for operation	32
Characterization of the ECR ion source LEGIS extraction system and its low energy beam transport line at Legnaro National Laboratories	32
ECRIS operation and developments at TRIUMF	33
Ion source upgrades at MedAustron ion therapy center	33
Recent achievements in the production of metallic ion beams with the CAPRICE ECRIS at GSI	34
Numerical design of an innovative superconducting magnetic trap for probing β -decay in ECR plasmas	35
Advances in PIC simulation of 2.45 GHz ECR ion sources	35
Modification of the flexible plasma trap for high-intensity metal ion beams production	36
Mixed carbon and helium ion beams for simultaneous heavy ion radiotherapy and radiography: an ion source perspective	37
3D simulations of the CAPRICE ECRIS extraction system	37
Status and perspectives of the PANDORA experiment: investigating β -decays in magnetized plasmas	38
Extrapolation of axis-symmetric magnetic fields in MDIS and ECRIS	39

TUA: Oral Session MC4 / 4

Design of a new iron plug for the TRIUMF ECRIS charge state booster

Author: Joseph Adegun¹

Co-authors: Friedhelm Ames¹; Oliver Kester¹

¹ TRIUMF

Corresponding Author: jadegun@triumf.ca

This paper presents an innovative solution to address the issue of asymmetric dipole fields in the injection region of the TRIUMF electron cyclotron resonance ion source charge state booster. The asymmetric fields arise from a wide gap in the booster's injection soft iron plug, which allows the connection of the RF waveguide to the plasma chamber. Simulations have revealed that singly charged ions, injected for charge breeding, experience deflection and get lost due to the asymmetric magnetic fields instead of being effectively captured by the plasma, thereby diminishing the efficiency of the charge state booster. To rectify this problem, a novel iron plug with an enlarged inner diameter, which allows the RF waveguide to connect to the plasma chamber with no gap was designed. Furthermore, this new design necessitates alterations to the injection electrodes and plasma chamber of the booster. Additionally, the waveguide and gas-inlet windows were repositioned to ensure better RF coupling into the plasma cavity. By eliminating the gap and implementing these design changes, it is anticipated that the TRIUMF charge state booster will operate at the same overall efficiency as other PHOENIX boosters.

Footnotes:

Funding Agency:

Natural Sciences and Engineering Research Council of Canada (NSERC) and TRIUMF

I have read and accept the Privacy Policy Statement:

Yes

MOP: Monday Poster Session / 5

Characterization of the 2.45 GHz DREEBIT ECRIS via optical spectroscopy

Author: Maria Molodtsova¹

Co-authors: Alexandra Philipp¹; Erik Ritter¹

¹ DREEBIT GmbH

Corresponding Authors: maria.molodtsova@dreebit.com, alexandra.philipp@dreebit.com

ECR ion sources are widely used to provide ions for various experimental setups. DREEBIT GmbH aims to industrialize this type of ion source technology for efficient and reliable use in, e. g., hadron cancer therapy as well as ion implantation of semiconductors. Our goal is to build table-top sized ion sources which can easily be handled as part of a larger machine such as a particle accelerator or target irradiation facility, thereby fulfilling high requirements on beam current, quality, stability as well as reproducibility in serial production. To achieve this, we have already optimized the microwave injection system and magnetic plasma confinement by introducing a simple method to allow for injection of circularly polarized waves and adjusted the magnetic field distribution which led to an 80 % increase of beam current. In the present work, we show how optical emission spectroscopy was used to gain deeper information about the plasma of this specific type of ion source, independent

from its ion extraction system. The plasma characterization includes studies of the electron energy distribution and the density of atomic and molecular hydrogen showing that the previous design changes of introducing circularly polarized microwaves and optimizing the magnetic field distribution have led to a well-optimized ECR ion source concerning plasma heating and proton production inside the plasma, indicating how the source performance can be enhanced in further steps.

Footnotes:**Funding Agency:****I have read and accept the Privacy Policy Statement:**

Yes

MOA: Oral Session MC1 / 6**High intensity highly charged ion beams production and operation at IMP****Author:** Liangting Sun¹**Co-authors:** Beimin Wu¹; Cheng Qian¹; Enmin Mei¹; Hongwei Zhao¹; Jibo Li¹; Jindou Ma¹; Li Zhu¹; Libin Li¹; Lixuan Li¹; Shijun Zheng¹; Wang Lu¹; Wei Wu¹; Wenhui Zhang¹; Xianjin Ou¹; Xinyu Wang²; Xuezheng Zhang¹; Yucheng Feng¹¹ *Institute of Modern Physics, Chinese Academy of Sciences*² *Paul Scherrer Institut***Corresponding Author:** sunlt@impcas.ac.cn

Charged by the existing operation facility HIRFL and HIAF one of the next generation heavy ion facilities under construction, high intensity high-charge state heavy ion beams production is in the high priority of research and development. For this purpose, several high performance ECR ion sources have been successively developed and put in routine operation. The recently developed FECR or the First 4th generation ECR ion source has employed the cutting-edge technologies for the development of a hybrid superconducting magnet using Nb₃Sn and NbTi superconductors. Operating at 28~45 GHz, FECR will give its first plasma and intense beam production. Other than ion sources development, new technologies development and new insights into high performance ECR ion source have led to increasingly ion beam intensities increase in both cw or pulsed modes. In this talk, high performance ion source development will be presented. A general review of the recent high intensity ion beam production progress at IMP and the routine operation for heavy ion accelerators will be made.

Footnotes:**Funding Agency:**

National Natural Science Foundation of China (Grant Nos. 12025506, 11427904)

I have read and accept the Privacy Policy Statement:

Yes

WEA: Oral Session MC6 / 7

Compact 2.45 GHz PMECR ion sources developed for accelerator based radiation therapy facilities at Peking University

Author: ShiXiang Peng¹

Co-authors: Bujian Cui¹; Tenghao Ma¹; Wenbin Wu¹; Kai Li¹; Yicheng Dong¹; Zhiyu Guo¹; Jia-er Chen²

¹ Peking University

² National Natural Science Foundation of China

Corresponding Authors: math1125@pku.edu.cn, wbwu@pku.edu.cn, 1700061306@pku.edu.cn, rrlikai@163.com, sxpeng@pku.edu.cn, chenjer@mail.nsf.gov.cn, zhyguo@pku.edu.cn, dongyc@buaa.edu.cn

Recently, Accelerator Based Radiation Therapy (ABRT) facilities for cancer treatment, that includes ion therapy and BNCT, have been bloomed up rapidly and is being established as a future modality to start a new era of in-hospital facilities around the world. A high current, small emittance, easy maintenance, long lifetime, high stability and reliability ion source is crucially important for those ABRT facilities. Research on this kind of characters ion source has been launched at Peking University (PKU) ion source group for more than 30 years and some exciting progresses, such as hundred mA H⁺/N⁺/O⁺ etc. beam current, less than 0.2 pi.mm.mrad emittance, a continue 300 hours non-sparking CW proton operation record have been achieved. Recently, we also involved in the ABRT campaign by in charging of ion sources. In this paper, we will summarize the several compact PKU 2.45 GHz permanent magnet ECR sources (PMECR) that were developed for proton therapy machines and BNCT facilities. The individual structure of the sources as well as the LEBT along with the commissioning results will be presented then.

Footnotes:

Funding Agency:

National Natural Science Foundation of China (Grant Nos.11975036, 11775007)

I have read and accept the Privacy Policy Statement:

Yes

MOP: Monday Poster Session / 8

Intense pulsed uranium ion beams production with ECRISs

Author: Lixuan Li¹

Co-authors: Jibo Li¹; Jindou Ma¹; Wenhui Zhang¹; Yucheng Feng¹; Denis Hitz¹; Hongyi Ma¹; Wang Lu¹; Liangting Sun¹; Hongwei Zhao¹

¹ Institute of Modern Physics, Chinese Academy of Sciences

Corresponding Author: lilixuan@impcas.ac.cn

Intense pulsed uranium ion beam production is essential for heavy ion accelerators (especially for synchrotrons) in operation and those under construction. Although metallic beam production is tricky, based on our earlier study, intense uranium beams can be expected when operating a electron cyclotron resonance (ECR) ion source especially in afterglow mode. In this study, we aim to produce intense uranium beams with LECR4 and SECAL-II (Superconducting ECR ion source with Advanced design in Lanzhou No. II) ion sources in afterglow modes. The experimental results will be reported in this presentation.

Footnotes:

Funding Agency:**I have read and accept the Privacy Policy Statement:**

Yes

WEA: Oral Session MC6 / 9**Characterization of D⁺ species in the 2.45 GHz ECRIS for 14-MeV neutron production****Author:** Sudhirsinh Vala¹**Co-authors:** HL Swami¹; Mitul Abhangi¹; Rajesh Kumar¹; Ratnesh Kumar¹¹ *Institute for Plasma Research***Corresponding Author:** sudhir@ipr.res.in

The Institute for Plasma Research has set up a 14-MeV neutron generator facility. The stability, quality, and repeatability of the D⁺ ion beam are critical parameters for ensuring the reliable operation of the neutron generator. Hence, a 2.45 GHz ECR ion source has been installed to produce the deuterium beam. The primary D beam characteristics are assessed by varying extraction voltage, microwave power, gas flow, and solenoid current of the ECRIS. By optimizing these parameters, the maximum design beam current is achieved. The D ion beam contains various species, including D⁺, D₂⁺, D₃⁺, and impurities. Accurate measurement of the D⁺ content within the D ion beam is the key parameter for a neutron generator. Multiple experiments were conducted to determine the D⁺ species and optimise the ECRIS parameters for maximum production of D⁺ species. Two beam current measurement devices, the DCCT and the Faraday Cup, were installed in the beamline to measure the total deuterium beam current and D⁺ beam current, respectively. Notably, the variation in the D⁺ fraction primarily depends on the operating parameters of the ECRIS, such as extraction voltage, microwave power and gas flow. This paper presents the results of the D⁺ ion current as a function of extraction voltage, microwave power, and gas flow rate. Understanding and characterizing the D⁺ species are essential steps toward achieving stable and efficient neutron production in fusion applications.

Footnotes:**Funding Agency:****I have read and accept the Privacy Policy Statement:**

Yes

THA: Oral Session MC1&MC2 / 10**High performance highly-charged ECR ion sources and matching with high-intensity heavy ion accelerator facility****Author:** Hongwei Zhao¹**Co-author:** Liangting Sun¹¹ *Institute of Modern Physics, Chinese Academy of Sciences*

Corresponding Author: zhaohw@impcas.ac.cn

Five ECR ion sources operating at 18-45 GHz microwave frequency are being operated or under commissioning to deliver highly-charged ion beams for high-intensity heavy ion cyclotron and linac accelerators at IMP in order to meet different requirements from the accelerators and physics experiments. One of the key issues for the ECRIS and accelerator physicists is how to match the highly-charged ECR ion sources with the accelerators and maximize performance of the accelerators from the point of view of beam intensities, charge states and costs. This paper will discuss how a highly-charged ECR ion source could match with a high-intensity heavy ion accelerator performance cost effectively on the basis of our operation experiences with the five ECR ion sources and the accelerators. If a new high-intensity heavy ion cyclotron or linac would be designed and built, performance and cost can be compared in detail for the cyclotron with an ECR ion source delivering Xe^{20+} and Xe^{35+} , and for the linac with an ECR ion source delivering U^{35+} and U^{55+} . Finally, it has been demonstrated that development of a highly-charged ECR ion source producing intense beams is more performance-cost-effective for a high-intensity heavy ion accelerator.

Footnotes:

Funding Agency:

I have read and accept the Privacy Policy Statement:

Yes

TUP: Poster Session / 11

Operation with the LAPECR3 ion sources for cancer therapy accelerators

Author: Jiaqing Li¹

Co-authors: Cheng Qian¹; Hui Wang¹; Jindou Ma¹; Liangting Sun¹; Wang Lu¹; Xuezheng Zhang¹; Yun Cao¹

¹ *Institute of Modern Physics, Chinese Academy of Sciences*

Corresponding Author: lijiaqing@impcas.ac.cn

An all-permanent magnet electron cyclotron resonance ion source-LAPECR3 (Lanzhou All Permanent magnet Electron Cyclotron Resonance ion source No.3) had been developed as the C^{5+} ion beam injector of Heavy Ion Medical Machine (HIMM) accelerator facility since 2009 in China. The first HIMM demo facility was built in Wuwei city in 2015, which had been officially licensed to treat patients in early 2020. The facility has been proven to be very effective, and more than 1000 patients have been treated so far. In order to prevent ion source failure, each facility employs two identical LAPECR3 ion sources to supply C^{5+} beam. At present, there are eight HIMM facilities under construction or in operation, and more than 16 LAPECR3 ion sources have been built. In order to improve the performance of the ion source for long term operation, some techniques were employed to optimize source performance and to avoid the damage of key equipment. This paper will introduce the operation status of LAPECR ion sources at these HIMM facilities and present the latest results of carbon beam production.

Footnotes:

Funding Agency:

I have read and accept the Privacy Policy Statement:

Yes

TUP: Poster Session / 12

An electrostatic ion beam transport system for intense proton source

Author: Qi Wu¹

Co-authors: Yuguo Liu¹; Liangting Sun¹; Hongwei Zhao¹

¹ *Institute of Modern Physics, Chinese Academy of Sciences*

Corresponding Author: wuq@impcas.ac.cn

The Ion Source Group has undertaken a R&D project of a compact low energy injector. The project is the development of an intense proton source and low energy beam (LEBT) for a transportable neutron source. The specific characteristics of the injector are low power consumption, compact and low beam emittance. An electrostatic low energy beam transport with a double Einzel-Lens setup is used to deliver 30 keV H⁺ beam to the entrance of a 2.5 MeV RFQ. A 2.45 GHz ECR ion source was adopted to provide 15 emA H⁺, H₂⁺ and H₃⁺ beams with a duty factor of 3 %. The fabrication, assembly and beam commissioning have been completed at IMP. The injector composed the 2.45 GHz ECR ion source and its LEBT was very compact, with a length of 900 mm. The beam current at the LEBT exit was about 16 mA with a pulse length of 300 μs and a repetition frequency of 50 Hz. In this paper, the studies of beam intensities, beam transmission efficiency in LEBT, beam emittance and mismatch factor are presented and discussed.

Footnotes:

Funding Agency:

I have read and accept the Privacy Policy Statement:

Yes

TUP: Poster Session / 13

Analysis of beam characteristic variations in the 14.5 GHz ECR ion source at RAON

Author: Jeong Il Heo¹

Co-authors: Hyung Jin Kim¹; In-Seok Hong¹

¹ *Institute for Basic Science*

Corresponding Author: jiheo@ibs.re.kr

RAON (Rare isotope Accelerator complex for ON-line experiments) is a heavy ion accelerator under construction in Daejeon, South Korea. RAON plans to operate a 28 GHz Electron Cyclotron Resonance Ion Source (ECRIS) with a fully superconducting magnet and is currently operating a 14.5 GHz ECR ion source with a fully permanent magnet. The 14.5 GHz ECRIS was manufactured by PANTECHNIK and installed in our beamline in September 2020. The initial beam conditioning of RAON was conducted using the 14.5 GHz ECR ion source with ⁴⁰Ar⁹⁺ and ⁴⁰Ar⁸⁺ beams. Additionally, beam tests were performed with protons, ⁴He²⁺, and oxygen. During these experiments, an unusual phenomenon was observed: the characteristics of the beam changed despite no variations in the parameters. This was consistently noted during some of the beam tests. We hypothesized several

potential causes for this phenomenon and analyzed them through experiments. In this paper, we discuss the results of these analyses.

Footnotes:

Funding Agency:

I have read and accept the Privacy Policy Statement:

Yes

MOD: Oral Session MC1&MC7 / 14

Development of deuterium-deuterium compact neutron source

Author: Andoni Perez¹

Co-authors: Andrés Roldán²; Iñigo Arredondo¹; Javier Praena²; Joaquin Portilla¹; Jorge Feuchtwanger³; Victor Etxebarria¹

¹ *University of the Basque Country*

² *Universidad de Granada*

³ *Ikerbasque, Basque Foundation for Science*

Corresponding Authors: joaquin.portilla@ehu.es, andoni.perez@ehu.es, victor@we.lc.ehu.es, inigo.arredondo@ehu.es, amroldan@ugr.es, jpraena@ugr.es, jorge.feuchtwanger@ehu.es

In the present work, we will present the status of the deuterium-deuterium (D-D) neutron source that is being developed in collaboration between the University of Granada and the University of the Basque Country (Spain).

Our neutron source consists of an ECR ion source which accelerates a deuteron beam towards a deuterated target. The ionization to achieve the deuterium plasma is achieved by radiating the cylindrical ERC plasma chamber with a magnetron 2.45 GHz signal and an 875 G magnetic field generated by 6 NdFeB magnets located around the plasma chamber. Moreover, a cylindrical alumina RF window is used to keep the vacuum status from the ambient pressure condition inside the WR340 and helping the plasma to ignite.

Once the plasma is generated, the deuterons are extracted from the plasma chamber using a Pierce electrode geometry and three other electrostatic lenses, fixed to different negative potentials. The beam is accelerated towards copper target disk with a deuterated titanium mesh fixed to -100 kV which generates the desired neutron radiation.

There are several applications of D-D neutron sources across scientific and industrial domains. In case of University of Granada and its deep relation with IFMIF-DONES neutron source, it is worthy to mention that we plan to carry out experiments for determining the cross-sections of relevant isotopes in the studies of IFMIF-DONES to a better simulation of the behaviour of such material under high neutron flux irradiation.

Footnotes:

Funding Agency:

I have read and accept the Privacy Policy Statement:

Yes

TUP: Poster Session / 15

Tests of a low-energy pepperpot based on a micro-channel plate for high current protons sources 4D-emittance characterization

Author: Anna Thézé¹

Co-authors: Augustin Dubois²; Guillaume Ferrand¹; Olivier Tuske²

¹ *Commissariat à l'Energie Atomique et aux Energies Alternatives*

² *Commissariat à l'Energie Atomique*

Corresponding Authors: anna.theze@cea.fr, augustin.dubois@cea.fr

In the scope of high current protons sources characterization, the CEA is working on a 4D-emittancemeter based on the pepperpot technology. After some unsuccessful developments with phosphorous scintillators, we decided to test micro-channel plates (MCP) for measurements of proton beams at very low energy (typically between 50 and 100 keV). MCP are supposed to resist to proton beams at very low energy better than scintillators. This work presents some results for MCPs with an ALISES source on the BETSI test bench.

Footnotes:

Funding Agency:

I have read and accept the Privacy Policy Statement:

Yes

TUP: Poster Session / 16

RF and multipactor simulations in the plasma chamber of the SILHI proton source

Authors: Guillaume Ferrand¹; Mathias Barant¹

Co-authors: Augustin Dubois²; Juliette Plouin²; Olivier Tuske²

¹ *Commissariat à l'Energie Atomique et aux Energies Alternatives*

² *Commissariat à l'Energie Atomique*

Corresponding Authors: guillaume.ferrand@cea.fr, mathias.barant@cea.fr

In the scope of high current protons sources simulations, we tried to simulate the plasma chamber of the SILHI proton source with HFSS. This work focuses on the RF and multipactor simulation close to the boron nitride window.

Footnotes:

Funding Agency:

I have read and accept the Privacy Policy Statement:

Yes

TUD: Oral Session MC3 / 17

Time-resolved measurement of ion beam energy spread variation due to kinetic plasma instabilities in CW and pulsed operation of an ECRIS

Author: Ville Toivanen¹

Co-authors: Juuso Huovila²; Hannu Koivisto¹; Olli Tarvainen³

¹ *University of Jyväskylä*

² *University of Eastern Finland*

³ *Science and Technology Facilities Council*

Corresponding Author: ville.a.toivanen@jyu.fi

The energy spread of ion beams extracted from Electron Cyclotron Resonance (ECR) ion sources is influenced by plasma conditions such as the plasma potential, and effects taking place in the beam formation region. Kinetic plasma instabilities have a significant impact on the plasma properties, and consequently on the ion beam energy spread. We present experimental results of time-resolved energy spread behaviour when kinetic plasma instabilities are present in CW and pulsed operation of the JYFL 14 GHz ECR ion source. It is shown that the instability-induced energy spread variation corresponds to a momentary plasma potential increase up to several kV from the steady-state value of 10–30 V. The method for measuring the time-resolved energy spread variation is presented, and the consequences of the energy spread and the underlying plasma potential variation for ECRIS operation are discussed.

Footnotes:

Funding Agency:

I have read and accept the Privacy Policy Statement:

Yes

MOP: Monday Poster Session / 18

ALISES II source is still alive

Author: Olivier Delferriere¹

Co-authors: Augustin Dubois²; Olivier Tuske²; Yannick Gauthier²; Yannick Sauce²

¹ *Commissariat à l'Energie Atomique et aux Energies Alternatives*

² *Commissariat à l'Energie Atomique*

Corresponding Author: olivier.delferriere@cea.fr

Developments of ECR intense light ion sources is an important research axis of the Laboratory of Study and Development of Accelerator at CEA-Saclay. Starting from the SILHI proton source in the 90's to inject the IPHI accelerator, several SILHI-type sources have been realized and installed for high intensity proton or deuteron accelerators for international projects like IFMIF, FAIR or SPIRAL2. From 2011, we started new R&D program on high intensity ECR compact ion sources with the ALISES source family.

The results obtained with the first ALISES source prototype gave us the main goals for the design of ALISES II source that runs several months on our 50 kV test bench BETSI and was dismantled at the end of 2016 to upgrade the test bench to 100 kV. But this source was never reinstalled and has been replaced by the ALISES III sources that runs on BETSI up to now.

Recently, ALISES II ion source and its equipment is reassembled to be restarted on BETSI for beam characterization before sending it to MIRROTRON factory in Hungary as injector of proton for neutron beam facility.

This paper describes the setup on BETSI and proton beam characteristics obtained by emittance measurements, spatial species proportion analysis with Wien filter and current optimization. Installation at MIRROTRON factory is also reported.

Footnotes:

Funding Agency:

I have read and accept the Privacy Policy Statement:

Yes

TUP: Poster Session / 19

Wien Filter upgrade and measurement for BETSI test bench

Authors: Augustin Dubois¹; Olivier Tuske¹

Co-authors: Olivier Delferriere²; Yannick Gauthier¹; Yannick Sauce¹

¹ *Commissariat à l'Energie Atomique*

² *Commissariat à l'Energie Atomique et aux Energies Alternatives*

Corresponding Authors: yannick.sauce@cea.fr, augustin.dubois@cea.fr, olivier.tuske@cea.fr, olivier.delferriere@cea.fr, yannick.gauthier@cea.fr

During first operation of SILHI in 1995 at CEA Saclay, a velocity filter diagnostic (Wien Filter) was installed on the LEPT, analyzing the 100 mA of protons at 95 keV. The device was used many years providing beam proportion measurements on the beam axis. Unfortunately, it was damaged while handling and was no longer working as intended. This paper describes the maintenance and upgrade of the diagnostic as well as the first beam proportion figures with ALISES 2 and ALISES 3 ion sources.

Footnotes:

Funding Agency:

I have read and accept the Privacy Policy Statement:

Yes

MOP: Monday Poster Session / 20

ALISESv3 ion source in various configuration along the year

Author: Olivier Tuske¹

Co-authors: Augustin Dubois¹; Olivier Delferriere²; Yannick Gauthier¹; Yannick Sauce¹

¹ *Commissariat à l'Energie Atomique*

² *Commissariat à l'Energie Atomique et aux Energies Alternatives*

Corresponding Author: olivier.tuske@cea.fr

ALISESv3 is a very compact light ion source that has been developed at CEA Saclay in 2018. The easy maintenance procedure of this source allowed us to test many different configurations. On the BETSI test bench equipped with an single Alisson Scanner and a pair a solenoid/deviator, we studied the extraction energy influence, we changed the number of electrodes in order to extract different kind of ions other than protons. This paper will describe briefly the ALISES 3 ion source and will present some results that we gathered in a year.

Footnotes:

Funding Agency:

I have read and accept the Privacy Policy Statement:

Yes

MOP: Monday Poster Session / 21

Study of noble gas memory effect of ECR3 at ATLAS

Author: Robert Scott¹

Co-authors: Jake McLain ¹; Michael Paul ²; Richard Vondrasek ¹; Sutanu Bhattacharya ²

¹ Argonne National Laboratory

² The Hebrew University of Jerusalem

Corresponding Author: scott@phy.anl.gov

Over the past three decades a portion of the accelerated beam time at the Argonne Tandem Linac Accelerator System (ATLAS) has been reserved for ultra-sensitive detection of argon radioisotopes. A unique noble-gas accelerator mass spectrometry (NOGAMS) technique [*] at ATLAS combines electron cyclotron resonance ion source (ECRIS) positive ion production, acceleration up to ~6 MeV/u and detection methods for separating isobars and other m/q contaminants. The ECR3 ion source was chosen for such experiments due to the limited scope of material introduced into the plasma chamber, inferring a lower background production compared to ECR2. A recent ³⁹Ar/⁴²Ar NOGAMS experiment has highlighted a need to understand the beam production of material that is no longer being actively introduced into the ECRIS, known as memory effect. A quantitative study of source memory was performed to determine the decay characteristics of argon in the ECR3 ion source. Results of this study as well as details of setup and operation of ECR3 for NOGAMS experiments are presented.

Footnotes:

- M. Paul et al., Nucl. Instr. and Methods in Phys. Research B 456, 222 (2019), <http://dx.doi.org/10.1016/j.nimb.2019.04.003>

Funding Agency:

This work was supported by the U.S. Department of Energy, Office of Nuclear Physics, under Contract No. DE-AC02-06CH11357.

I have read and accept the Privacy Policy Statement:

Yes

WEB: Oral Session MC6 / 22

Beam intensity prediction using ECR plasma images and machine learning

Author: Yasuyuki Morita¹**Co-authors:** Ayumi Kasagi²; Keita Kamakura³; Naoya Oka⁴; Takahiro Nishi⁵¹ *Osaka University*² *Rikkyo University*³ *University of Tokyo*⁴ *National Institute of Information and Communications Technology*⁵ *Nishina Center for Accelerator-Based Science*

Long-term beam stability is one of the important issues in supplying multivalent heavy ion beams using an Electron Cyclotron Resonance Ion Source (ECRIS). When the beam intensity drops for long-term operation, the ECRIS parameters need to be tuned to restore the original beam intensity. Continuous measurement of the beam intensity using a Faraday cup (FC) is impractical while the beam is in use. We have had to rely on an unreliable method of monitoring the total drain current to estimate the beam intensity during beamtime. To resolve this issue, we propose a new method for predicting the beam intensity at FC using machine learning. Our approach incorporates plasma images, captured through a hole in the beam extraction electrode, and operating parameters as input data for the machine learning model. In short-term test datasets, our model has successfully produced rough predictions of the beam intensity. This presentation will detail the prediction model and its prediction results on the test data.

Footnotes:**Funding Agency:****I have read and accept the Privacy Policy Statement:**

Yes

MOP: Monday Poster Session / 23

Development of a 100 mA-class CW microwave ion source for industrial accelerators

Author: Ryu Murase¹**Co-authors:** Hirohiko Murata¹; KAZUHIRO YOKOYAMA²; Nobuaki Takahashi¹; Yukio Mikami¹¹ *Sumitomo Heavy Industries Ltd.*² *Sumitomo Heavy Industries, Ltd.***Corresponding Author:** ryu.murase@shi-g.com

Industrial accelerators are currently employed in a multitude of fields, including semiconductor manufacturing and medicine. In recent years, there has been a growing demand to enhance the irradiation throughput of industrial accelerators, which necessitates the development of high-current ion sources. In this study, we developed a 2.45 GHz off-resonance 100 mA-class CW microwave ion source that can be integrated into industrial accelerators. The design was optimized for proton beam generation. The plasma chamber and the matching section, which is responsible for matching the impedance of the waveguide and the plasma chamber, were designed using a combination

of an analytical approach and finite element electromagnetic field analysis. The electromagnets for generating the off-resonance magnetic field to increase the plasma density were designed using finite element magnetostatic field calculations. The design of the single-hole, three-electrode beam extraction system, which operates in acceleration-deceleration mode, was performed using beam orbit calculations that take into account space-charge effects. The design and fabrication have been completed, and beam tests are now underway. In the presentation, in addition to the design of the ion source, we will also report on the preliminary results that were obtained in the beam test.

Footnotes:**Funding Agency:****I have read and accept the Privacy Policy Statement:**

Yes

TUP: Poster Session / 24

Planned optimization of the ion sources on the HIT test bench

Author: Tim Winkelmann¹**Co-authors:** Andreas Peters¹; Bernd Naas¹; Rainer Cee¹; Thomas Haberer¹¹ Heidelberg Ionenstrahl-Therapie Centrum**Corresponding Author:** tim.winkelmann@med.uni-heidelberg.de

The Heidelberg Ion Beam Therapy Center (HIT) is a hospital-based treatment facility in Germany. Since the first treatments in 2009, more than 8.500 patients have been irradiated with protons or carbon ions and since July 2021 with helium ions. At HIT, three Supernanogan ion sources supplied by Pantechnik are in operation around the clock for therapy up to 335 days a year.

A 4th Supernanogan ECR ion source is installed at the HIT test bench. The test bench is currently being prepared for a measurement campaign that will begin in October. The aim of the investigations is to obtain more beam current for the carbon ions used in therapy by feeding two microwave frequencies in parallel. We expect that this experiment will provide a better understanding of the ionization process in the ion source. In the first step we will feed 14.5 GHz and an extra frequency near the resonance frequency of 14.5 GHz. ± 0.5 GHz. In the second step we will feed in 14.5 GHz and 18 GHz.

To characterize and evaluate the beam quality in this setup, we will use the pepperpot a 4D emittance measuring device. In addition, it is possible to measure the beam current and the beam profile at the test bench.

This article provides an overview of the planned developments on the test bench.

Footnotes:**Funding Agency:****I have read and accept the Privacy Policy Statement:**

Yes

MOP: Monday Poster Session / 25

Performance of the hybrid ECR ion source development at IMP

Authors: Cheng Qian¹; Liangting Sun¹**Co-authors:** Hongyi Ma¹; Jiaqing Li¹; Jindou Ma¹; Li Zhu¹; Libin Li¹; Shijun Zheng¹; Tongjun Yang¹; Wang Lu¹; Wenhui Zhang¹; Xing Fang¹; Xudong Wang¹; Yucheng Feng¹; Zhang Peng¹¹ *Institute of Modern Physics, Chinese Academy of Sciences***Corresponding Authors:** sunlt@impcas.ac.cn, qianc@impcas.ac.cn

Highly charged ion beams have wide applications in fundamental sciences such as nuclear physics and atomic and molecular physics, as well as in applied industries including heavy ion cancer therapy and semiconductor processing. The Electron Cyclotron Resonance (ECR) ion source is one of the most effective devices for producing highly charged ion beams. Based on the requirement for a relatively simple structure and high performance ECR ion source, a Hybrid superconducting Electron Cyclotron Resonance ion source Advanced in Lanzhou (HECRAL) has been designed and constructed at the Institute of Modern Physics (IMP). The magnetic confinement of the ion source is realized by the axial mirror field provided by four superconducting solenoids while the radial hexapole magnetic field supplied by non-Halbach hexapole permanent magnet. The axial injection and extraction magnetic fields reach 3.4 T and 1.7 T, respectively. The radial field at the plasma chamber wall of a 100 mm inner diameter is above 1.4 T. This paper will present a detailed magnet design. The ion source was commissioned and operated at a frequency of 18 GHz with 3 kW power, approaching the performance of the Superconducting Electron Cyclotron Resonance ion source with Advanced design in Lanzhou (SECRAL) operating at the same frequency. Several high intensity high charge state ion beams have been produced, such as 723 eμA O⁷⁺, 70 eμA Ar¹⁶⁺, 95 eμA Kr²⁶⁺, 21 eμA Xe³⁵⁺, 120 eμA Bi³³⁺, and 88 eμA U³⁷⁺, and so on.

Footnotes:**Funding Agency:****I have read and accept the Privacy Policy Statement:**

Yes

TUC: Oral Session MC3 / 26

Simulation of Bremsstrahlung emission in ECRIS and its dependence on the magnetic confinement

Author: Andrea Cernuschi¹**Co-author:** Thomas Thuillier¹¹ *Laboratoire de Physique Subatomique et de Cosmologie***Corresponding Author:** cernuschi@lpsc.in2p3.fr

A Monte Carlo (MC) code dedicated to the electron dynamics in ECRIS was recently completed with a new functionality, allowing to simulate Bremsstrahlung photon emission from the volume interaction of electrons with charged particles inside the plasma. The simulation qualitatively reproduces the experimental anisotropy of the photon spectral temperature previously reported. The effects of variations in the magnetic field minimum Bmin and in the extraction peak on both the electron energy distribution function and the Bremsstrahlung emission are also investigated and reported. The simulation results confirm that only changes in Bmin influences the hot energy tail of the EEDF

*. The MC high electron statistics allows studying with unprecedented details the location and mechanism responsible for the hot electrons generation in ECRIS, highlighting the crucial role of Bmin in this process.

Footnotes:

- J. Benitez, C. Lyneis, L. Phair, D. Todd, and D. Xie, IEEE Transactions on Plasma Science 45, 1746 (2017).

Funding Agency:

This work is supported by Agence Nationale de la Recherche with the contract # 21-ESRE-0018 EQUIPEX+ NEWGAIN.

I have read and accept the Privacy Policy Statement:

Yes

TUA: Oral Session MC4 / 27

ECR2 performance upgrades at ATLAS

Author: Jake McLain¹

Co-authors: Richard Vondrasek¹; Robert Scott¹

¹ *Argonne National Laboratory*

Corresponding Author: jmclain@anl.gov

The user requests for higher beam energies and intensities have driven the decision to upgrade the ECR2 ion source at the Argonne Tandem Linac Accelerator System. Multiple upgrades are in progress with the expected outcome of dramatically increased ECR2 beam intensities and charge state capabilities. The magnetic upgrades include integrating an improved hexapole permanent magnet array* that provides the ion source radial fields, reworking the magnetic materials surrounding the plasma chamber, and installing a new cooling system for the electromagnetic solenoids that govern the ion source axial fields. The new hexapole and higher solenoid magnet operating currents will increase the ion source magnetic fields and support the use of 18 GHz RF heating, further increasing the ECR2 beam capabilities. Following these improvements and subsequent source performance, simulations of beam transport devices on the ion source platform will need to be revisited for transmission of high intensity beams. Details of these upgrade projects and simulations of the ion optics are presented.

Footnotes:

[*] Vondrasek R, McLain J, Scott R 2024 J. Phys.: Conf. Ser. 2743 012044

Funding Agency:

This work was supported by the U.S. Department of Energy, Office of Nuclear Physics, under Contract No. DE-AC02-06CH11357.

I have read and accept the Privacy Policy Statement:

Yes

MOP: Monday Poster Session / 28

Use of a 2.45 GHz ECR ion source for the Neutron Target Demonstrator project

Author: Stephane Melanson¹

Co-authors: Anand George¹; Morgan Dehnel¹

¹ *Dehnel - Particle Accelerator Components & Engineering, Inc.*

Corresponding Author: stephane@d-pace.com

D-Pace has licensed a 2.45 GHz ECR ion source from Neutron Therapeutics. The ion source will be used for the Neutron Target Demonstrator project at Los Alamos National Laboratory where 10 mA of singly charge krypton ions at 50 keV are required with a normalized 4-RMS emittance of less than 1 mm·mrad. The goal of the project is to create a reverse kinematics neutron capture reaction with ⁸⁴Kr ions. Due to the high radiation environment that the ion source will be subjected to, a solid state microwave power supply will be used instead of the traditional magnetron for the experiment. The main advantage of the solid state power supply is that the output is transmitted by a coax cable instead of a waveguide, so the power supply can be located a long distance away from the ion source without the need for a complicated and expensive waveguide. The other advantage of the solid state device is that the frequency can be varied from 2.4 GHz to 2.5 GHz. This gives the operator an extra degree of freedom for tuning the ion source and also allows for the use of permanent magnets instead of solenoids while still having the ability to tune the ECR condition. We present how the frequency variation affects the beam parameters with both the solenoid and the permanent magnet versions of the ion source.

Footnotes:

Funding Agency:

I have read and accept the Privacy Policy Statement:

Yes

TUB: Oral Session MC8 / 29

Simulation of the Bremsstrahlung emission induced by electrons impinging the plasma chamber walls of the ASTERICS ECRIS

Author: Thomas Thuillier¹

Co-authors: Andrea Cernuschi¹; Benjamin Cheymol¹; Christophe Peaucelle¹; Damien Simon²; Francis Vezzu¹

¹ *Laboratoire de Physique Subatomique et de Cosmologie*

² *Commissariat à l'Energie Atomique*

Corresponding Authors: cernuschi@lpsc.in2p3.fr, thomas.thuillier@lpsc.in2p3.fr, vezzu@lpsc.in2p3.fr, peaucelle@lpsc.in2p3.fr, damien.simon@cea.fr, cheymol@lpsc.in2p3.fr

A new electron cyclotron resonance ion source (ECRIS) named ASTERICS is under development for the NEWGAIN project, aiming at building a new injector for the SPIRAL2 accelerator at GANIL. A Monte Carlo code dedicated to the electron dynamics in ECRIS is used to investigate the local energy, position and velocity distribution of electrons impinging on the plasma chamber wall of ASTERICS. These quantities are presented for both the injection and extraction planes and the radial chamber wall. Results show that the electron energy distribution function is different on each of these three surfaces and that the electron velocity direction to the walls is deeply anisotropic. This

data is next used as an input in a Fluka 3-dimensional model including the ASTERICS ECRIS mechanics, a simplified low energy beam line and the experimental cave in which the ion source will be installed. The x-ray flux characteristics around the source are presented. The shielding thickness and its location are studied to grant the safe passage of personnel around the ECRIS location in the accelerator building.

Footnotes:**Funding Agency:**

This work is supported by Agence Nationale de la Recherche with the contract # 21-ESRE-0018 EQUIPEX+ NEWGAIN.

I have read and accept the Privacy Policy Statement:

Yes

MOC: Oral Session MC1 / 30

Challenges in production of intense metallic ion beams at IMP

Author: Wang Lu¹

Co-authors: Cheng Qian¹; Hongwei Zhao¹; Hongyi Ma¹; Liangting Sun¹; Libin Li¹; Lixuan Li¹; Xuezhen Zhang¹; Yucheng Feng¹

¹ *Institute of Modern Physics, Chinese Academy of Sciences*

Corresponding Authors: lilixuan@impcas.ac.cn, luwang@impcas.ac.cn, zhxzh@impcas.ac.cn, zhaohw@impcas.ac.cn, lilibin@impcas.ac.cn, fengyc@impcas.ac.cn, mahy04@impcas.ac.cn, qianc@impcas.ac.cn, sunlt@impcas.ac.cn

Since the development of inductive heating oven in 2019 [1], several intense highly charged metallic ion beams have been produced for different requirements at IMP (Institute of Modern Physics). According to the material characteristics, we used different forms of metal materials, including metal elements (Cr, Mn, Ni, Fe), oxides (UO₂), fluoride or iodide (ZrF₄, SrF₂, CsI), etc. Detail experiments setup and testing results will be presented in this contribution.

Footnotes:**Funding Agency:****I have read and accept the Privacy Policy Statement:**

Yes

TUP: Poster Session / 31

Characterization of an proton ECR ion source for low beam current

Author: Pello Usabiaga¹

Co-authors: Iratxe Ariz²; Iñigo Arredondo¹; Joaquin Portilla¹; Jon Vivas¹; Jorge Feuchtwanger³; Jose Mari Seara Eizaguirre²; Victor Etxebarria¹

¹ *University of the Basque Country*

² *Fundación TEKNIKER*

³ *Ikerbasque, Basque Foundation for Science*

Corresponding Authors: jorge.feuchtwangerm@ehu.eus, pellousabiaga@gmail.com

In this paper we analyze the behavior of a low beam current proton ECR ion source for linac. During the operation of the source, as a function of the operating parameters we have observed a complex behavior. The state of the plasma is highly dependent on the input parameters, and in some cases even bi-stable conditions can be achieved showing abrupt changes in the state. To try to understand this behavior we carried out a series of experiments varying the input parameters both sequentially and randomly to avoid following the same path every time. Thanks to these experiments we have been able to observe the change in the luminosity of the plasma, which is an indirect measure of the degree of ionization in the plasma, along with the changes in reflected and transmitted RF power delivered to the source. We also characterized the relation between the outside temperature of the ion source chamber walls and the plasma. In addition to this we have analyzed the resulting extracted ion beam using a pepperpot and a faraday cup. We have observed that our beam doesn't have one dominant species and has three species that are found in comparable quantities.

Footnotes:

Funding Agency:

Basque Government, Department of Industry, Elkartek KK-2022/00026
Basque Government, Department of Education, IT1533-22

I have read and accept the Privacy Policy Statement:

Yes

MOP: Monday Poster Session / 32

Non-intrusive plasma state detection using machine learning

Author: Ander Fernández-Rua¹

Co-authors: Iñigo Arredondo¹; Raquel Justo¹; Pello Usabiaga¹; Jorge Feuchtwanger²

¹ *University of the Basque Country*

² *Ikerbasque, Basque Foundation for Science*

Corresponding Authors: inigo.arredondo@ehu.eus, anderrua@gmail.com

In this paper we present the methodology used to acquire the data needed to obtain and train a neural network that will be used in an ECR source to infer the state of the plasma. All the data is the combination of the control signals and a set of non-intrusive measurements that can be accessed during normal operation.

For this purpose, machine learning techniques are explored. First, a set of characterisation experiments are carried out in which the state of the plasma is detected for different operating conditions that are fed to a clustering algorithm. Second, a supervised learning paradigm is adopted to train a neural network that is capable of determining the state of the plasma at different working states. The variables that are controlled are: the input RF power and gas flow, the non-intrusive measurements that are acquired are: transmitted and reflected RF power and a ccd camera is used to measure the relative luminosity of the plasma. Based on these variables the state of the plasma is determined. This methodology has been applied to the low-power ECR source in which low-density hydrogen plasmas are generated at the IZPILab laboratory of the University of the Basque Country.

Footnotes:

Funding Agency:**I have read and accept the Privacy Policy Statement:**

Yes

MOP: Monday Poster Session / 33**Status report on 60 GHz ECRIS activity****Author:** Thomas Andre¹**Co-authors:** Andrea Cernuschi¹; Christophe Peaucelle¹; Etienne Labussière¹; François Debray²; Julien Angot¹; Maud Baylac³; Olivier Zimmermann¹; Patrick Sole¹; Pierre-Olivier Dumont¹; Thomas Thuillier¹¹ *Laboratoire de Physique Subatomique et de Cosmologie*² *Laboratoire National des Champs Magnétiques Intenses*³ *CNRS –LPSC***Corresponding Author:** thomas.andre@lpsc.in2p3.fr

SEISM (Sixty gigahertz Ion Source using Megawatt magnets) is an electron cyclotron resonance ion source operating at the frequency of 60 GHz using a gyrotron producing high intensity HF pulse (up to 1 ms/300 kW/2 Hz). The prototype is based on an axial cusp magnetic geometry using polyhelix coils (installed at the LNCMI facility in Grenoble) generating a closed ECR surface at 2.1 T.

Since 2019 and the restart of the project, several experimental campaigns were carried out using oxygen support gas. Beam production was studied using the setting of the source aiming to reproduce the ion current densities of 1 A/cm² previously measured. Set up and recent experimental results, will be presented.

Furthermore, in the frame of the PACIFICS project (funded by French National Research Agency under the Equipex Program), a new 60 GHz ion source will be built, where polyhelix will be replaced by superconducting coils and the source will be installed at LPSC for easier availability. A new extraction system will be built in order to transform the observed high current density into a target ion beam intensity of ~100 mA.

This paper will present a preliminary study of the new extraction system, built upon the principles developed by Vybin*. The system's design and optimization is carried out using COMSOL Multiphysics and IBSIMU simulation tools, ensuring precise modeling of electric field fields and ion trajectories.

Footnotes:

- S S Vybin et al 2020 Plasma Sources Sci. Technol. 29 11LT02

Funding Agency:**I have read and accept the Privacy Policy Statement:**

Yes

MOA: Oral Session MC1 / 35

Development towards intense uranium ion beam production of the RIKEN 28 GHz SC-ECRIS

Author: Glynnis Mae Saquilayan¹

Co-authors: Jun-ichi Ohnishi²; Osamu Kamigaito²; Takashi Nagatomo²; Yoshihide Higurashi²

¹ *Nishina Center for Accelerator-Based Science*

² *RIKEN Nishina Center*

Corresponding Author: glynnismae.saquilayan@riken.jp

High intensity Uranium $^{238}\text{U}^{35+}$ ion beams are produced in the 28 GHz superconducting electron cyclotron resonance ion source(SC-ECRIS) and accelerated to high energies in the Radioactive Isotope Beam Factory(RIBF) at RIKEN. We report the current progress of the SC-ECRIS. Intense beam operation of U^{35+} was made possible through the development of high temperature ovens with optimized consumption rates of more than 10 mg/h and beam intensities reaching up to 250 μA . With efforts toward realizing even higher beam intensities, it is now more important to optimize beam optics and minimize losses in the accelerator. This has stressed the study of emittance size and its growth factors. Measurement using a slit-collector type emittance monitor showed beam emittances that increase proportionally with the extraction current. For beam currents of 100 to 150 μA , the beam emittances had minimal variation and remain at $0.15 \pi \cdot \text{mm} \cdot \text{mrad}$ for an extraction current of 5.5 mA. Differences between the normalized horizontal and vertical rms emittances were observed and horizontal emittances tend to be lower and less affected by beamline components. Using measured horizontal emittances coupled with a reference model calculation of space charge induced beam emittances, the $^{238}\text{U}^{35+}$ beam emittance ϵ_0 defined by the ion source was estimated. A systematic study using the calculated ϵ_0 to understand its correlation between the ECR parameters and magnetic field strength is currently ongoing.

Footnotes:

Funding Agency:

I have read and accept the Privacy Policy Statement:

Yes

TUP: Poster Session / 36

Optical diagnostic studies of the electron cyclotron resonance plasma produced in the GTS-LHC ion source

Author: Bichu Bhaskar¹

Co-authors: Detlef Kuchler¹; Toke Koevener²

¹ *European Organization for Nuclear Research*

² *No affiliation*

Corresponding Author: bichu.bhaskar@cern.ch

The GTS-LHC electron cyclotron resonance (ECR) ion source is an integral part of the chain of accelerators at CERN. It produces the heavy ion beams which are accelerated using a series of accelerators from LINAC up to the LHC. The ion beams are extracted from an ECR plasma generated at the GTS-LHC ion source, however, there has not yet been a non-invasive diagnostic device to study the plasma. This research focuses on the implementation of an optical diagnostics and studies the optical emission spectra (OES) as a monitor of the performance of the ion source. Furthermore, we explore the correlation between spectral properties and changing source parameters, offering insights into the behaviour of the ion source, which in turn helps in fine-tuning of the source. Specifically, the

study concentrates on long-term OES analysis spanning several weeks, focusing on the production of magnesium and lead ions using the GTS-LHC ion source.

Footnotes:

Funding Agency:

I have read and accept the Privacy Policy Statement:

Yes

MOP: Monday Poster Session / 37

Light ions from the GTS-LHC ion source for future physics at CERN

Author: Detlef Kuchler¹

Co-authors: Bichu Bhaskar¹; Giulia Bellodi¹; Maciej Slupecki¹; Richard Scrivens¹

¹ *European Organization for Nuclear Research*

Corresponding Author: detlef.kuchler@cern.ch

Starting from 2028, physics programmes using ions at CERN have requested lighter ions than the lead usually produced. The Working Group on Future Ions in the CERN Accelerator Complex has been mandated to assess the feasibility of the production and operation of these new ion species. The ion beam production from two of the chosen elements, krypton and magnesium, was studied in the GTS-LHC ion source, and the preliminary results of beam intensity, stability and emittance will be presented, as well as proposed modifications to improve performance.

Footnotes:

Funding Agency:

I have read and accept the Privacy Policy Statement:

Yes

MOP: Monday Poster Session / 38

Continuous data-driven control of the GTS-LHC ion source at CERN

Authors: Detlef Kuchler¹; Verena Kain¹

Co-authors: Borja Rodriguez Mateos¹; Michael Schenk²; Niky Bruchon¹; Simon Hirlaender³

¹ *European Organization for Nuclear Research*

² *Ecole Polytechnique Fédérale de Lausanne*

³ *University of Salzburg*

Corresponding Authors: detlef.kuchler@cern.ch, verena.kain@cern.ch

Recent advances with the CERN infrastructure for machine learning allows to deploy state-of-the-art data-driven control algorithms for stabilising and optimising particle accelerator systems. This contribution summarises the results of the first tests with different continuous control algorithms to optimise the intensity out of the CERN LINAC3 source. The task is particularly challenging due to the different latencies for control parameters that range from instantaneous response, to full response after only ~30 minutes. The next steps and a vision towards full deployment and autonomous source control will also be discussed.

Footnotes:

Funding Agency:

I have read and accept the Privacy Policy Statement:

Yes

MOA: Oral Session MC1 / 39

Operation and development of the 28 GHz electron cyclotron resonance (ECR) ion source at the facility for Rare Isotope Beams (FRIB)

Author: Guillaume Machicoane¹

Co-authors: Haoyu Cheng ²; Junwei Guo ²; Larry Tobos ¹; Randall Rencsok ¹

¹ *Michigan State University*

² *Facility for Rare Isotope Beams, Michigan State University*

Corresponding Author: machicoa@nscl.msu.edu

FRIB has now been in operations for over 2 years and deliver beam to the nuclear physics users with high reliability and high efficiency. Two ECR ion sources are used to produce a high charge state heavy ion beam including a 28 GHz capable, superconducting ECR that has been used for the scientific program since the beginning of 2023. Central to the performance of the FRIB accelerator are a superconducting linac and a charge stripping system allowing the primary beam to reach energies above 200 MeV/u and a beam power on the fragmentation target above 10 kW with only a few tens of microamperes required from the ECR ion source. This beam power was achieved for many primary beams including Uranium and has been used routinely for experiments over the past year. FRIB plan to increase the beam power available to users in steps from 20 kW next year and ultimately up to 400 kW. This presentation goes over the operation of the ECR ion sources at FRIB with emphasis on the 28 GHz ECR ion source including solid beam production and plan for intensity ramp up using our 10 kW 28 GHz gyrotron and operation of the superconducting magnet. Finally plans for a second and third superconducting ion source are presented.

Footnotes:

Funding Agency:

Work supported by the U.S. Department of Energy Office of Science under Cooperative Agreement DE-SC0023633, the State of Michigan, and Michigan State University.

I have read and accept the Privacy Policy Statement:

Yes

TUP: Poster Session / 40

A novel design of superconducting magnet for ECR ion source

Author: Enmin Mei¹¹ *Institute of Modern Physics, Chinese Academy of Sciences***Corresponding Author:** meiem@impcas.ac.cn

Since the powerful capability of producing high charge state ions for heavy ions and the long lifetime of the ECR ion source is deemed one of the most robust ion source types. So far, the 3rd generation ECR built with NbTi superconductor has a wonderful performance reference to the ECR used by LBNL and IMPCAS for a long time. However, this type of ECR has not got a well spread and further development either in accelerator systems or in other areas. The reason is its inefficiency of electromagnetic design and the complexity of mechanical structure design and technical realization. Aim to conquer this embarrassing situation of the 3rd ECR magnet. This paper proposes a novel structure design that combines minimal layers of solenoids and Discrete-Cosine-Theta coils that are embedded in the machined grooves. Besides the high magnetic field generation efficiency, this structure can also reduce the accumulation of the coils' Lorentz forces. The details of the electromagnetic mechanical design of this new magnet structure will be described in this paper.

Footnotes:**Funding Agency:****I have read and accept the Privacy Policy Statement:**

Yes

TUA: Oral Session MC4 / 41

The electrostatic deceleration of ions injected into an ECRIS CB plasma

Author: Julien Angot¹**Co-authors:** Alessio Galatà ²; Olli Tarvainen ³; Pierre Chauveau ⁴; Thomas Thuillier ¹¹ *Laboratoire de Physique Subatomique et de Cosmologie*² *Istituto Nazionale di Fisica Nucleare*³ *Science and Technology Facilities Council*⁴ *Grand Accélérateur Nat. d'Ions Lourds***Corresponding Author:** angot@lpsc.in2p3.fr

The capture of the 1+ beam is a key parameter in the charge breeding process with an ECRIS-Charge Breeder as it greatly influences the 1+N+ conversion efficiency. The shape of the efficiency vs incident ion energy « Delta V » curve originally led to the theory of slowing down of the injected ions essentially by cumulative small-angle scatterings in collisions with the buffer gas ions. Recent experiments carried out with the PHOENIX charge breeder at LPSC tends to show that the electrostatic deceleration plays a greater role than historically considered. For this study, we varied the CB plasma potential by acting on the microwave power parameter and by measuring the optimum injection energy for sodium, rubidium and cesium ions. Both i) the correlation between the plasma potential and optimum injection energy parameters and ii) the independence of the optimum energy value as a function of the incident ion mass support the new model based on a slowing down essentially electrostatic.

Footnotes:**Funding Agency:****I have read and accept the Privacy Policy Statement:**

Yes

TUC: Oral Session MC3 / 42**Microwave transmission measurements at the VENUS ECR ion source****Author:** Janilee Benitez¹**Co-authors:** Damon Todd¹; Sage Holter¹¹ *Lawrence Berkeley National Laboratory***Corresponding Author:** jybenitez@lbl.gov

The VENUS electron cyclotron resonance (ECR) ion source uses injected 18 and 28 GHz microwave power to resonantly energize electrons for plasma ionization. Waveguide antennas detecting 18 and 28 GHz microwaves located after the extraction electrode exit aperture of the source are used to measure the transmitted microwave power under different source and plasma conditions. In addition, an antenna is placed in the 28 GHz waveguide to measure 18 GHz microwaves that make it back out, during 18 GHz only operation. The relationship between the transmitted and reflected power is investigated. Measuring the transmitted power can aid in understanding how to efficiently couple the microwaves to the plasma so as to achieve the maximum source output. The transmitted power, which is inversely related to the absorbed power, is dependent on the neutral gas pressure, and the minimum magnetic field B_{\min} . The production of $^{16}\text{O}^{6+}$ is also compared with the transmitted power.

Footnotes:**Funding Agency:****I have read and accept the Privacy Policy Statement:**

Yes

TUP: Poster Session / 43**Efficient injection of high-intensity light ions from an ECR ion source into an RFQ accelerator****Author:** Chuan Zhang¹**Co-author:** Eduard Boos¹¹ *GSI Helmholtzzentrum für Schwerionenforschung GmbH***Corresponding Author:** c.zhang@gsi.de

This study investigates an efficient injection of high-intensity light ions from an Electron Cyclotron Resonance (ECR) ion source into a Radio Frequency Quadrupole (RFQ) accelerator. An often-adopted solution for the beam matching between an ion source and an RFQ is to apply two solenoids as a Low Energy Beam Transport (LEBT) section. There are also other solutions which skip the LEBT section and inject the ion-source output beam directly into an RFQ e.g. the so-called Direct Plasma Injection Scheme (DPIS). For this study, a compact electrostatic LEBT using an einzel lens as well as an efficient RFQ based on a special design method have been developed to achieve high transmission of a 60 mA proton beam. Additionally, the RFQ design has been also checked with the LEBT removed. The design and simulation results will be presented.

Footnotes:**Funding Agency:****I have read and accept the Privacy Policy Statement:**

Yes

MOP: Monday Poster Session / 44**Role of ECRISs to reveal astrochemical processes****Author:** Richárd Rác¹**Co-authors:** Béla Sulik¹; Duncan Mifsud¹; Gergő Lakatos¹; Nigel Mason²; Péter Herczku¹; Rahul Kumar Kushwaha¹; Robert McCullough³; Sandor Biri¹; Sergio Ioppolo⁴; Sándor Kovács¹; Thomas Field³; Zoltan Juhasz¹; Zoltan Perduk¹¹ *Institute for Nuclear Research*² *Centre for Astrophysics and Planetary Science (CAPS), School of Physics and Astronomy, University of Kent*³ *Queen's University Belfast*⁴ *Aarhus University***Corresponding Author:** rracz@atomki.hu

Electron Cyclotron Resonance (ECR) Ion Sources are widely used as the first stage of high energy (MeV –GeV) accelerators providing ion beams for versatile research fields including nuclear and particle physics. However, in the Atomki the 2nd generation 14 GHz ECR ion source operates as a standalone device opening the possibility to develop research areas requiring low energy ion beams in the range of 0.5 keV –100 keV. One of this research fields is called astrochemistry. Astrochemistry has been the recipient of continuously increasing interest in the last few decades. The relevance of interstellar molecules to the emergence of life is strong motivation for better comprehending the astrochemical mechanisms leading to their formation and destruction. For this purpose, a new beamline and a special experimental chamber AQUILA (Atomki-Queen's University Ice Laboratory for Astrochemistry) were installed and commissioned recently to the Atomki ECRIS. AQUILA has been purposefully designed to study the chemical evolution of ices analogous to those that may be found in the dense interstellar medium or the outer Solar System as a result of their exposure to low energy ion beams. In this contribution the carefully designed ion transport system, the way of the well-controlled irradiation methods and also the main features of the AQUILA analytic system will be presented.

Footnotes:**Funding Agency:****I have read and accept the Privacy Policy Statement:**

Yes

MOP: Monday Poster Session / 45

ECR ions sources at CRC in UCLouvain, Belgium

Author: François-Philippe Hocquet¹

Co-authors: Laurent Standaert²; Nancy Postiau³

¹ *Louvain Catholic University*

² *Université catholique de Louvain*

³ *Université Catholique de Louvain*

Corresponding Authors: laurent.standaert@uclouvain.be, francois-philippe.hocquet@uclouvain.be

The Cyclotron laboratory (CRC) was created in 1972 with the installation of the cyclotron “CYCLONE” ($K_b = 110$) in Louvain-la-Neuve, Belgium. Until late 90’s, this cyclotron was dedicated to research in nuclear physics (ISOL RIBs, used for nuclear astrophysics measurements), nuclear chemistry and medicine (neutron and proton therapy). The CRC now mainly delivers ions beams for industrial applications as radiation hardness tests of electronic devices for space applications or micro-porous membrane production.

Our center has extensive experience (historically) with homemade ECR sources designed and built. Two ECR ions sources are used for our daily routine operations. The oldest, SCAMPI (Source Compacte Améliorée pour le Meilleur et pour le Pire, 6 GHz, 2 coils and permanent magnet, first beam in 1996), was used to produce heavy ions beams until the new ECR source came into operation and is mainly used nowadays to produce $^{40}\text{Ar}^{11+}$ and $^{40}\text{Ar}^{12+}$ beams. The second, BLUE WHALE (17,3 GHz, 3 coils and permanent magnet, first beam in 2016), is nowadays to produce heavy ions cocktail, including $^{124}\text{Xe}^{35+}$.

This poster presentation will present a status report on the variate applications, the performance of our ECR ion sources and our ongoing developments.

Footnotes:

Funding Agency:

I have read and accept the Privacy Policy Statement:

Yes

MOP: Monday Poster Session / 46

GANIL cyclotron and ion source for industrial application

Author: Romain Frigot¹

Co-authors: Mickael Dubois¹; Bertrand Jacquot¹

¹ *Grand Accélérateur Nat. d’Ions Lourds*

Corresponding Author: frigot@ganil.fr

The GANIL (Grand Accélérateur National d’Ions Lourds) in Caen produces up to 20 % of the beam times dedicated to industrial applications, such as the irradiation of electronic components.

The SAGA (Space Application at GAnil) project aims to increase beam times for these applications in the future in order to meet demand from French and European industries.

In this context, one of the challenges is to be able to switch rapidly from one beam to another in order to optimize the beam time available to industry. To meet these requirements, CIME's cyclotron could be an interesting device: it is capable of accelerating beams up to 20 MeV/A for light elements, and it can be used as a mass separator to select the desired beam. In order to supply stable ion beams to the CIME cyclotron, the charge breeder installed on the SPIRAL1 facility has been tested and adapted to provide a stable cocktail-type beam with a very close A/Q. Details of the project and initial results will be described.

Footnotes:**Funding Agency:****I have read and accept the Privacy Policy Statement:**

Yes

TUD: Oral Session MC3 / 47

A novel test-facility for ECRIS plasma diagnostics: optical spectroscopy, X-ray imaging and spectroscopy, mm-wave polarimetry

Author: Eugenia Naselli¹**Co-authors:** Angelo Pidotella¹; Bharat Mishra¹; Bianca Peri¹; David Mascali¹; Giorgio Finocchiaro¹; Giorgio Mauro¹; Giuseppe Torrisi¹; Richárd Rác²; Sandor Biri²¹ *Istituto Nazionale di Fisica Nucleare*² *Institute for Nuclear Research***Corresponding Author:** eugenia.naselli@lns.infn.it

In the frame of the PANDORA project and the SAMOTHRACE ecosystem (Italian PNRR in the EU Next Gen Program contest), two new plasma diagnostics testbenches –PYN-HO and VESPRIZ.0 setups –have been developed at INFN-LNS, with the aim to design and improve detectors and techniques beyond the state of art. The PYN-HO prototype is conceived to operate in four configurations: two of them to enhance high resolution X-ray imaging and space-resolved spectroscopy, also including X-ray tomography using multi pin-hole CCD systems, involving algorithms for Single Photon-Counted and High-Dynamic-Range analysis, with related calibrations via SDD; the other two are dedicated to high energy resolution diffractometric spectroscopic measurement in the X-ray and optical domains, based on micrometric gratings. The VESPRIZ.0 mm-wave polarimeter is based on an innovative superheterodyne approach to measure plasma-induced Faraday rotation from Lissajous figure detection and estimate the plasma line-integrated density. **Prototypes can be installed in ECRIS for several plasma physics studies****, such as investigations of plasma structure, confinement dynamics, instabilities and turbulence, in-plasma and plasma vessel elemental composition, local thermodynamic parameters, etc. which are directly related to ion beam performances in ECRIS. The design and features of the prototypes and the first characterizations performed with Ar plasma in the INFN-LNS Flexible Plasma Trap will be presented.

Footnotes:

D. Mascali et al., *Universe* 8 80, 2022E. Naselli et al., *Condens. Matter* 7(1) 5, 2022G. Torrisi et al., *Front. Astron. Space Sci.* 9 949920, 2022**E. Naselli, *Eur. Phys. J. Plus* 138: 599, 2023

Funding Agency:**I have read and accept the Privacy Policy Statement:**

Yes

TUB: Oral Session MC8 / 48

Progress in 3D self-consistent full wave-PIC modelling of space resolved ECR plasma properties

Author: Angelo Pidotella¹

Co-authors: Alessio Galatà¹; Giorgio Mauro¹; Bharat Mishra¹; Eugenia Naselli¹; Giuseppe Torrisi¹; David Mascali¹

¹ *Istituto Nazionale di Fisica Nucleare*

Corresponding Author: pidotella@lns.infn.it

We present updates of a simulation suite to model in-plasma ion-electron dynamics, including self-consistent electromagnetic (EM) wave propagation and ion population kinetics to study atomic processes in ECR plasmas. The EM absorption is modelled by a heuristic collisional term in the cold dielectric tensor. However, we are stepping beyond the cold approximation, modelling the hot tensor with non-collisional RF wave damping. The tool calculates steady-state particle distributions via a full wave-PIC code and solves for collisional-radiative process giving atomic population and charge state distribution. The scheme is general and applicable to many physics'cases of interest for the ECRIS community, including the build-up of the charge-state-distribution and the plasma emitted X-ray and optical radiation. We present its last updates and future perspectives, using as a case-study the PANDORA scenario. We report about studying in-plasma dynamics of injected metallic species and radioisotopes ionisation efficiency for different injection conditions and plasma parameters. The code is capable of reconstructing space-resolved plasma emissivity, to be directly compared to plasma emission measurements, and modelling plasma-induced modification of radioactivity.

Footnotes:

Funding Agency:

I have read and accept the Privacy Policy Statement:

Yes

MOC: Oral Session MC1 / 49

A novel inductive oven design for the production of high current, metal ion beams

Author: Damon Todd¹

Co-author: Janilee Benitez¹

¹ *Lawrence Berkeley National Laboratory*

Corresponding Author: dstodd@lbl.gov

Essential to the proposed search for element 120 at LBNL's 88-Inch Cyclotron is the continual delivery of over a particle microamp of $^{50}\text{Ti}^{12+}$ for weeks-long campaigns spanning many months. The fully-superconducting ECR ion source VENUS will be the injector source for these runs, and we have developed a new inductive oven design that can survive VENUS'high magnetic fields while injecting metallic gas into the plasma with high efficiency. The new oven employs a vertical susceptor to

permit use with metals that melt before outgassing sufficiently, while also allowing a rotation of the oven's material exit toward the plasma center for better conversion efficiency to the produced beam. The performance of VENUS with this oven has been outstanding: as reported here, 282 MeV $^{50}\text{Ti}^{12+}$ beams with stable currents between 1.0 and 1.5 μA have been delivered for superheavy element searches over multiple ten-day runs.

Footnotes:**Funding Agency:**

This work was supported by the U.S. Department of Energy, Office of Science, Office of Nuclear Physics under contract number DE-AC02-05CH11231 (LBNL).

I have read and accept the Privacy Policy Statement:

Yes

WEA: Oral Session MC6 / 50

A plasma based, charge state stripper for heavy ion accelerators

Author: Gerard Rodrigues¹

¹ *Inter University Accelerator Centre*

Corresponding Author: gerosro@gmail.com

The ionization of ions to a higher charge state is of central importance for the development of new Accelerator Facilities like FAIR [1], and the resulting cost savings. Currently, mainly gas and foil strippers are used for increasing the charge state even after using a high performance ECR ion source in a typical Accelerator chain. Even when the foil or/and gas stripper efficiency or lifetime has proved to be less than optimal, as these alternatives either require great effort or are practically not suitable for smooth operation in the long term.

Free electrons in highly ionized plasmas [2,3] can be effectively used for improving the charge state of heavy ions as the rates of radiative recombination of free electrons are much smaller than those of electron capture on bound electrons, which leads to a substantial increase of the effective charge in a plasma compared to a cold-gas target of the same element. Theta and Z pinch plasmas are possible options which have been explored and experimentally studied at IAP, Frankfurt, Germany [4]. Typical electron line densities required to be achieved are in the range of 10^{16} to 10^{19} cm^{-3} and electron temperatures of the order of few tens of eV are found to be very favourable as per modelling with the FLYCHK code [5], but also extremely challenging. Such a plasma device, the challenges to be overcome, together with their design details will be presented.

Footnotes:

References

1. <https://fair-center.eu/>
2. Nardi E, Zinamon Z Phys. Rev. Lett. 49 1251 (1982)
3. T. Peter, J. Meyer-ter-Vehn, Energy loss of heavy ions in dense plasma. II. Nonequilibrium charge states and stopping powers, Phys. Rev. A 43 (1991) 2015–2030, <http://dx.doi.org/10.1103/PhysRevA.43.2015>
4. C.Teske, J.Jacoby, F.Senzel, W.Schweizer, Phys. Plasmas 17,043501(2010)
5. FLYCHK code: www-amdis.iaea.org

Funding Agency:

-

I have read and accept the Privacy Policy Statement:

Yes

WEB: Oral Session MC6 / 51

Applying machine learning techniques to the operation of the superconducting ECR ion source VENUS

Author: Damon Todd¹

Co-authors: Alex Kireeff ¹; Heather Crawford ¹; Janilee Benitez ¹; Marco Salathe ¹; Victor Watson ¹; Yue Shi Lai ¹

¹ *Lawrence Berkeley National Laboratory*

Corresponding Author: dstodd@lbl.gov

An operator of the superconducting ECR ion source VENUS tasked with optimizing the current of a specific ion species or finding a stable operating mode is faced with an operation space composed of ten-to-twenty knobs in which to determine the next move. Machine learning techniques are well-suited to multidimensional optimization spaces. Over the last three years we have been working to employ such techniques with the VENUS ion source. We will present how the introduction of computer control has allowed us to automate tasks such as source baking or to utilize optimization tools to maximize beam currents with no human intervention. Our more recent applications of Bayesian optimization and reinforcement learning to beam current maximization and the maintenance of long term source stability will also be presented. Finally, we will discuss control and diagnostic changes that we have employed to exploit the faster data collection and decision making abilities when VENUS is under computer control.

Footnotes:

Funding Agency:

This material is based upon work supported by the U.S. Department of Energy, Office of Science, Nuclear Physics program under Award Numbers DE-FOA-0002490 and DE-FOA-0002875

I have read and accept the Privacy Policy Statement:

Yes

TUP: Poster Session / 52

Transport of intense Bi and U beams into an RFQ

Author: Gerard Rodrigues¹

¹ *Inter University Accelerator Centre*

Corresponding Author: gerosro@gmail.com

A 48.5 MHz RFQ has been designed to transport and accelerate ²³⁸U⁴⁰⁺ (0.52 emA) and ²⁰⁹Bi³⁰⁺ (1.047 emA) beams extracted from a high performance ECR ion source. The RFQ design comprises of a pre-buncher built into the vanes to narrow the transmitted charge state distribution as much as

possible. The design parameters as a function of cell length is optimised on $^{209}\text{Bi}^{30+}$. It is shown that the losses of various ions without using an inlet aperture are inevitable, but by proper coating of the vanes of the RFQ, sputtering can be minimised to a great extent. Titanium shows better results when compared with gold or copper and this has been verified using the modelling results from SRIM. The design details of matching the ECR and the RFQ and the predicted performance will be presented.

Footnotes:

-

Funding Agency:

-

I have read and accept the Privacy Policy Statement:

Yes

THA: Oral Session MC1&MC2 / 55

Waveguide DC breaks with optimized impedance matching networks

Author: Michel Kireeff Covo¹**Co-authors:** Brien Ninemire¹; Damon Todd¹; Daniel Xie¹; Jaime Cruz Duran¹; Janilee Benitez¹; John Paul Garcia¹; Larry Phair¹; Michael Johnson¹; Patricius Bloemhard¹¹ *Lawrence Berkeley National Laboratory***Corresponding Author:** mkireeffcovo@lbl.gov

A custom 18 GHz waveguide DC break with a built-in impedance matching network, consisting of two inductive irises adjacent to a capacitive gap assembled around a quartz disk, was built for VENUS and simulated using the ANSYS High Frequency Structure Simulator, a finite element analysis tool. The DC break effectively doubled the RF power available for plasma production at the secondary frequency of 18 GHz while maintaining a DC isolation of 32 kV. Measurements of the forward and reflected power coefficients, performed with a network analyzer, showed excellent agreement with the simulations*. Additionally, an extended study was conducted to tailor the frequencies of 28, 35, and 45 GHz using WR-34, WR-28, and WR-22 waveguides with built-in impedance matching networks, aiming to predict performance for our upcoming 4th generation low-power, multi-frequency operation of the MARS-D ion source.

Footnotes:

- M. Kireeff Covo, et al., "Inductive Iris Impedance Matching Network for a Compact Waveguide DC Break," in IEEE Transactions on Microwave Theory and Techniques, early access (2024), DOI: 10.1109/TMTT.2024.3409470.

Funding Agency:

This work was supported by the Director, Office of Science, Office of Nuclear Physics, Division of Nuclear Physics, U.S. Department of Energy under Contract No. DE-AC02-05CH11231.

I have read and accept the Privacy Policy Statement:

Yes

MOB: Oral Session MC1 / 56

GANIL cyclotron ion sources: optimisation for operation

Author: Mickael Dubois¹

Co-authors: Benoit Osmond¹; Frederic Lemagnen¹; Nicolas Lechartier¹; Stéphane Hormigos¹; Vincent Metayer¹

¹ *Grand Accélérateur Nat. d'Ions Lourds*

Corresponding Author: dubois@ganil.fr

The GANIL (Grand Accélérateur National d'Ions Lourds) in Caen has been producing and accelerating stable and radioactive ion beams for nuclear physics, atomic physics, radiobiology and materials irradiation since 1982.

On cyclotrons facility, two ion sources (ECR4 and ECR4M) are used to produce around 4,000 hours per year of gaseous and metallic beams. Recently, studies have been carried out to find ways of optimizing beam characteristics (stability, intensities).

One of these involves improving the long-term stability of the beam, which is an important parameter for tuning the accelerator and for physics experiments. At the same time, this improved stability will also reduce the need of on-call interventions for ion source experts.

Other studies and tests have been carried out to increase the intensity and/or stability of the metal beams by adapting the injection of the ion source on ECR4/4M. Depending on the configuration, the gain shall be up to a factor of 2 on the charge state required for acceleration, and stability has also been improved compared to previous one.

Some details and results will be presented.

Footnotes:

Funding Agency:

I have read and accept the Privacy Policy Statement:

Yes

MOD: Oral Session MC1&MC7 / 57

Characterization of the ECR ion source LEGIS extraction system and its low energy beam transport line at Legnaro National Laboratories

Author: Giada Rachele Mascali¹

Co-authors: Luca Bellan²; Carmelo Sebastiano Gallo²; Denis Martini²; Paolo Francescon²; Michele Comunian²; Osvaldo Carletto²; Alessio Galatà²

¹ *Sapienza University of Rome*

² *Istituto Nazionale di Fisica Nucleare*

Corresponding Author: giadarachele.mascali@uniroma1.it

At INFN-Legnaro National Laboratories the heavy ions accelerator complex is fed with beams produced by a permanent magnet ECR source called LEGIS (LEGnaro ecrIS). Although suitable intensities and charge states to fulfil the requests of the users are normally guaranteed, the first part of the Low Energy Beam Transport line (LEBT) downstream of the ion source suffers from non-negligible losses and a lack of scalability when switching between ions with different mass-to-charge ratios, thus leading to a machine preparation time longer than would be desirable. These criticalities called

for a deep characterization of the beam coming out from the ion source, especially in the case of high charge states heavy ions production, normally showing the lowest intensities. This contribution describes the numerical studies performed on the extraction system of the LEGIS source and its LEBT. The physics case used is a $^{208}\text{Pb}^{31+}$ beam produced for a nuclear physics experiment in fall 2022. As will be shown, the results shed light on the reasons for the bad reproducibility and transmission, mostly due to aberrations induced on the extracted beam by the first optical elements.

Footnotes:**Funding Agency:****I have read and accept the Privacy Policy Statement:**

Yes

MOB: Oral Session MC1 / 58

ECRIS operation and developments at TRIUMF

Authors: Friedhelm Ames¹; Joseph Adegun¹; Christopher Charles¹; Keerthi Jayamanna¹; Oliver Kester¹; Brad Schultz¹

¹ TRIUMF

Corresponding Authors: jadegun@triumf.ca, bschultz@triumf.ca, ccharles@triumf.ca, okester@triumf.ca, ames@triumf.ca, keerthi@triumf.ca

Rare isotope beams are used at the ISAC facility at TRIUMF for studies mainly in nuclear and astrophysics, but also for applications ranging from material science to medicine. The isotopes are produced via the ISOL technique and ionized via a set of different ion sources depending on the application. In cases where highly charged ions are needed, charge state breeding is done with a 14.5 GHz PHOENIX ECR ion source from PANTECHNIK. The source has been operational for more than a decade providing a wide range of ions from Na to U at $A/Q < 7$ for post-acceleration. A second ECR ion source, a SUPERNANOGAN also from PANTECHNIK is used to provide highly charged ions from stable isotopes either for set-up and calibration for the rare isotope beams or for nuclear reaction studies with stable ions. The presentation will give a summary of results and will describe the challenges and improvements to the original sources. For the charge state breeding this is mainly increasing the efficiency and the purity of the delivered beams. In the case of the SUPERNANOGAN special emphasis is put on operational aspects to cover a wide range of elements and easy switchover. The latest in this series of improvements is the implementation of two frequency plasma heating in both ion sources.

Footnotes:**Funding Agency:****I have read and accept the Privacy Policy Statement:**

Yes

WEB: Oral Session MC6 / 59

Ion source upgrades at MedAustron ion therapy center

Author: Nadia Gambino¹

Co-authors: Greta Guidoboni¹; Matthias Kausel¹; Clemens Maderböck¹; Szymon Myalski¹; Liviu Penescu²; Valeria Rizzoglio¹; Claus Schmitzer¹

¹ *EBG MedAustron GmbH*

² *Abstract Landscapes*

Corresponding Author: nadia.gambino@medaustron.at

MedAustron is a synchrotron-based cancer therapy center providing proton and carbon ion beams in an energy range of 62–252 MeV/u and of 120–400 MeV/u, respectively. The facility has three clinical irradiation rooms, among which horizontal and vertical beam lines as well as a proton gantry are available for treatment. A fourth irradiation room is dedicated to non-clinical research and will additionally provide helium ion beams in the near future. The injector features three identical ECRIS operated at 14.5 GHz, two of which are used for proton and carbon ion beam production. The third ion source is used for helium beam generation as well as a test bench for future source upgrades. One of the latest upgrades, rolled-out clinically, is the switch of the carbon ion source from continuous wave operation to pulsed mode operation. In this work we present the main commissioning results obtained in pulsed mode and the beam properties measured up to the irradiation rooms. The results of ongoing source upgrade activities, for future potential clinical use, concerning the use of Double Frequency Heating mode for the proton source, improving the overall accelerator performances, will also be discussed.

Footnotes:

Funding Agency:

I have read and accept the Privacy Policy Statement:

Yes

MOC: Oral Session MC1 / 60

Recent achievements in the production of metallic ion beams with the CAPRICE ECRIS at GSI

Author: Alexander Andreev¹

Co-authors: Fabio Maimone¹; Jan Maeder¹; Michael Galonska¹; Ralf Lang¹; Ralph Hollinger¹

¹ *GSI Helmholtzzentrum für Schwerionenforschung GmbH*

Corresponding Authors: m.galonska@gsi.de, f.maimone@gsi.de, r.hollinger@gsi.de, r.lang@gsi.de, a.andreev@gsi.de, j.maeder@gsi.de

The GSI CAPRICE Electron Cyclotron Resonance Ion Source (ECRIS) provides highly-charged ion beams for various experiments at GSI, enabling the delivery of continuous wave (CW) metallic ion beams with low material consumption, which is crucial for producing high charge state ion beams from rare or extremely rare isotopes such as ⁴⁸Ca. These metallic beams are produced utilizing the thermal evaporation technique by resistively heated ovens. Due to the research groups' demand for higher beam intensities, increased ion currents of higher charge states are now necessary from the CAPRICE ECRIS.

A test campaign was conducted to establish and improve the production of high charge states of enriched ⁵⁴Cr and ⁵⁵Mn ion beams. During the tests, plasma images were captured using a CCD camera to support the operation and enable real-time monitoring of the material consumption. Additionally, a hot screen was used to protect the ceramic insulators in the extraction system from metal deposition, thereby improving the operational stability of the ECRIS. The application of an optical emission spectroscopy to monitor the stability of metallic ion beams during the operation with the

resistively heated ovens was also investigated. This contribution presents the operational experience, the intensities and stability achieved for the aforementioned elements. In addition, an update on a recent improvement involving a specialized oven preparation stand for better conditioning of the ovens is given.

Footnotes:

Funding Agency:

I have read and accept the Privacy Policy Statement:

Yes

THA: Oral Session MC1&MC2 / 61

Numerical design of an innovative superconducting magnetic trap for probing β -decay in ECR plasmas

Author: Giorgio Mauro¹

Co-authors: Giuseppe Torrisci¹; Angelo Pidotella¹; Eugenia Naselli¹; Filippo Russo¹; Bharat Mishra¹; Giorgio Finocchiaro¹; Alessio Galatà¹; Domenico Santonocito¹; David Mascali¹

¹ *Istituto Nazionale di Fisica Nucleare*

Corresponding Author: mauro@lns.infn.it

The main aim of Plasmas for Astrophysics Nuclear Decays Observation and Radiation for Archaeometry (PANDORA) project is to build a flexible magnetic plasma trap where plasma reaches a density $n_e \sim 10^{11} - 10^{15} \text{ cm}^{-3}$, and a temperature, in units of kT, $kT_e \sim 0.1 - 30 \text{ keV}$ in order to measure, for the first time, nuclear β -decay rates in stellar-like conditions.

Here we present the numerical design of the PANDORA magnetic system, carried out by using the commercial simulators OPERA and CST Studio Suite. In particular, we discuss the design choices taken to: 1) obtain the required magnetic field levels at relevant axial and radial positions; 2) avoid the magnetic branches along the plasma chamber wall; 3) find the optimal position for the set of plasma diagnostics that will be employed.

The magnetic trap has been conceived to be as large as possible, both in radial and axial directions, in order to exploit the plasma confinement mechanism on a bigger plasmoid volume. The plasma chamber will have a length of 700 mm and a diameter of 280 mm.

The magnetic trap tender procedure has been completed in June 2024 and the structure realization is expected to start in late 2024.

Footnotes:

Funding Agency:

I have read and accept the Privacy Policy Statement:

Yes

TUB: Oral Session MC8 / 62

Advances in PIC simulation of 2.45 GHz ECR ion sources

Author: Lorenzo Neri¹

Co-authors: Andrea Miraglia¹; Armando Coco²; Francesco Grespan¹; Giovanni Russo²; Giuseppe Castro¹; Luigi Celona¹; Michele Comunian¹; Ornella Leonardi¹; Santo Gammino¹; Sebastiano Boscarino²; giuseppe bilotta³

¹ *Istituto Nazionale di Fisica Nucleare*

² *Università degli Studi di Catania*

³ *Istituto Nazionale di Geofisica e Vulcanologia*

Corresponding Authors: celona@lns.infn.it, russo@dmi.unict.it, neri@lns.infn.it, michele.comunian@lnl.infn.it, giuseppe.bilotta@ingv.it, francesco.grespan@lnl.infn.it, castrog@lns.infn.it, ornella.leonardi@lns.infn.it, miraglia@lns.infn.it, gammino@lns.infn.it, armando.coco@unict.it, boscarino@dmi.unict.it

INFN-LNS effort in PIC development for ECR Ion Sources is growing, and the collaboration is enlarging. Simulation capability is essential to reveal phenomena that diagnostics cannot catch. The simulation incorporates 3D charged particle motion, 3D electromagnetic simulation with tensorial permittivity, 2D axial symmetric Poisson solver, density evolution of neutral and excited particles, interaction with conductive and insulating walls, and electrostatic beam extraction. Recent upgrades include an adaptive time step and Poisson solver optimisation, allowing simulation of a hundred microseconds, with a time step of 2×10^{-12} seconds, in one month of computation. The chemical model was extended to 32 reactions and now includes the first excited atomic level of H and the first excited vibrational level of H₂. The secondary electron emission and the charge accumulation on the dielectric surface of Boron Nitride disks were implemented, and their role in the plasma formation was disclosed. The actual validation phase, where simulation results are compared to experimental data, will be reported. The commissioning of the PS-ESS source shows a region where the source does not produce a beam, even if powered by 600 W of RF power. This behaviour was fully disclosed by simulation and will be presented. The role of the different resonances acting on the standard high current configuration (MDIS) and super stable configuration (HSMDIS*) will also be discussed.

Footnotes:

- L. Neri, L. Celona, "High Stability Microwave Discharge Ion Sources", Nature Scientific Reports 12, 3064 (2022) <https://doi.org/10.1038/s41598-022-06937-7>

Funding Agency:

I have read and accept the Privacy Policy Statement:

Yes

TUP: Poster Session / 63

Modification of the flexible plasma trap for high-intensity metal ion beams production

Author: Carmelo Sebastiano Gallo¹

Co-authors: Angelo Pidotella¹; Giada Rachele Mascali²; Salvatore Marletta¹; David Mascali¹; Giorgio Mauro¹; Santi Passarello¹; Antonio Domenico Russo¹; Giuseppe Torrisi¹; Alessio Galatà¹

¹ *Istituto Nazionale di Fisica Nucleare*

² *Sapienza University of Rome*

Corresponding Author: carmelogallo@lnl.infn.it

NQSTI (National Quantum Science and Technology Institute) is the enlarged partnership on QST established under the National Recovery and Resilience Plan (NRRP) funded by the European Union

–NextGenerationEU. In this framework, there is a growing interest in the availability of mA beams of singly charged (1+) metallic ions to realise quantum devices. To satisfy this request, the joint INFN Laboratories LNS and LNL proposed to modify the Flexible Plasma Trap (FPT), installed at LNS, thus transforming it into a simple mirror Electron Cyclotron Resonance Ion Source (ECRIS). This contribution describes the various technical solutions that will be adopted, foreseeing novel radial RF and gas/metal injection systems, focusing particularly on the design and simulations of a flexible extraction system capable of handling different beam intensities and ion species. Specifically, the project targets the production of high-intensity beams of singly charged ions such as Fe^+ , and Ba^+ , highlighting the versatility and innovation of the proposed modifications.

Footnotes:**Funding Agency:****I have read and accept the Privacy Policy Statement:**

Yes

MOB: Oral Session MC1 / 64**Mixed carbon and helium ion beams for simultaneous heavy ion radiotherapy and radiography: an ion source perspective****Author:** Michael Galonska¹**Co-authors:** Alexander Andreev¹; Christian Graeff¹; Fabio Maimone¹; Jan Maeder¹; Lennart Volz¹; Ralf Lang¹; Ralph Hollinger¹¹ *GSI Helmholtzzentrum für Schwerionenforschung GmbH***Corresponding Author:** m.galonska@gsi.de

Within the framework of research on simultaneous heavy ion radiotherapy and radiography, a mixed carbon/helium ion beam with a variable He percentage has been successfully established and investigated at GSI for the first time in order to study this new mode of image guidance for carbon ion beam therapy.

The mixed C/He ion beam was provided by the 14.5 GHz CAPRICE ECR ion source for the subsequent linac-synchrotron accelerator systems at GSI. Prior to that experiment, different ion combinations ($^{12}\text{C}^{3+}/^4\text{He}^+$ or $^{12}\text{C}^{4+}/^3\text{He}^+$) out of CH_4 or CO_2 have been investigated at the ECR test bench in terms of ion beam currents, stability, and C-to-He-fraction quantified by optical spectral lines and mass spectra. From an ion source perspective, it turned out that each of the different combinations comply with all the requirements of the experiments which successfully took place utilizing a $^{12}\text{C}^{3+}/^4\text{He}^+$ -ion beam with an energy of 225 MeV/u. Finally, both ions were simultaneously accelerated and extracted and characterised in the biophysics cave.

This paper briefly outlines some of the measurements obtained at the test bench and during the beam time from an ion source perspective.

Footnotes:**Funding Agency:****I have read and accept the Privacy Policy Statement:**

Yes

TUP: Poster Session / 65

3D simulations of the CAPRICE ECRIS extraction system

Author: Michael Händler¹

Co-authors: Alexander Andreev²; Fabio Maimone²; Giuliano Franchetti²; Jan Maeder²; Michael Galonska²; Ralf Lang²; Ralph Hollinger²

¹ *Goethe Universität Frankfurt*

² *GSI Helmholtzzentrum für Schwerionenforschung GmbH*

Corresponding Author: m.a.haendler@gsi.de

The simulation of the ion extraction from the Electron Cyclotron Resonance Ion Sources (ECRISs) is necessary for the optimization and development of the performance of ion sources.

Due to the magnetic field configuration of the ECRISs the calculations need to be performed in 3D. Therefore simulation programs based i.e. on C++ libraries like IBSimu were developed. In this work a physical model was implemented in IBSimu generating detailed 3D simulations of ion extraction from a CAPRICE-type ECRIS.

Simulations of multi-species Argon ion beam including Helium contribution as support gas extracted from CAPRICE are carried out. The study includes the effect of different space charge compensation degrees.

Furthermore, ion beams extracted with different plasma electrode apertures were analyzed in terms of ion beam current, beam profile, beam size, divergence angle, and beam quality.

In addition the simulation results were compared to experimental findings, i.e. ion beam intensities and beam profiles measured with viewing screens.

Footnotes:

Funding Agency:

I have read and accept the Privacy Policy Statement:

Yes

TUC: Oral Session MC3 / 66

Status and perspectives of the PANDORA experiment: investigating β -decays in magnetized plasmas

Author: David Mascali¹

Co-author: Domenico Santonocito¹

¹ *Istituto Nazionale di Fisica Nucleare*

Corresponding Author: davidmascali@lns.infn.it

This contribution deals with the upcoming PANDORA (Plasmas for Astrophysics, Nuclear Decay Observations and Radiation for Archaeometry) facility*, at INFN-LNS, Catania. PANDORA aims at measuring β -radioactivity rates and chemical element opacity in plasmas produced in an electron cyclotron resonance ion trap (ECRIT). The beta-decay rates are expected to vary of several orders of magnitude in a hot plasma, due to the interplay between the nuclear and atomic processes by the so-called bound-state-beta-decay mechanism (BSBD). Variations of decay rates have huge impact in astrophysical scenarios and cosmic nucleosynthesis processes, impacting on the chemical abundances in the Galaxy and in the early Universe. The PANDORA experimental setup will consist of: 1) a superconducting magnetic trap of 700 mm in length, 280 mm in diameter, operating

up to 21 GHz, in triple-frequency heating mode; 2) an array of 14 of high efficiency High Purity Germanium detectors used to measure the gamma-rays emitted as by-products of beta-decays; 3) a unique multi-diagnostics system to characterize the plasma, including mm-wave super-heterodyne interfero-polarimeter, Thomson scattering, two high-resolution optical spectrometers, two CCD pin-hole camera systems for X-ray spectroscopy, imaging and tomography, SDD and Si-pin detectors for volumetric spectroscopy, and a mass-spectrometer. The talk will give an overview about the status of the facility construction.

*D. Mascali et al., Universe 8 80, 2022

Footnotes:

Funding Agency:

I have read and accept the Privacy Policy Statement:

Yes

TUP: Poster Session / 67

Extrapolation of axis-symmetric magnetic fields in MDIS and ECRIS

Author: Giuseppe Castro¹

Co-authors: Luigi Celona¹; Grazia D'Agostino¹; Ornella Leonardi¹; Santo Gammino¹; Davide Siliato¹; Giacomo Costanzo¹

¹ *Istituto Nazionale di Fisica Nucleare*

Corresponding Authors: gammino@lns.infn.it, ornella.leonardi@lns.infn.it, castrog@lns.infn.it, costanzo@lns.infn.it, siliato@lns.infn.it, celona@lns.infn.it, dagostino@lns.infn.it

Microwave discharge ion sources (MDIS) and electron cyclotron resonance ion sources (ECRIS) are widely used to feed particle accelerators. Their magnetic field consists in an axis-symmetric magnetic field that can be produced by permanent magnets or coils with the aim of assuring plasma heating by electron cyclotron resonance and confining the plasma axially. In ECRIS, a sextupole is added for radial plasma confinement. The 3D configuration of the magnetic field is needed to simulate beam extraction and plasma particles motion in the plasma chamber. Due to mechanical constraints, the measurement of the magnetic field in the entire chamber volume is often difficult or not possible.

This work introduces a numerical method for magnetic field extrapolation in the whole ion source volume by experimental measurements of the magnetic field in the plasma chamber along the axis. The approach has been validated by comparing extrapolated values with experimental measurements.

Footnotes:

Funding Agency:

I have read and accept the Privacy Policy Statement:

Yes