



Contribution ID: 86 Contribution code: FRBC2

Type: Contributed Oral Presentation

## A systematic investigation of beam losses and position reconstruction techniques measured with a novel oBLM at CLEAR

Friday, 13 September 2024 11:20 (20 minutes)

Optical Beam Loss Monitors (oBLMs) allow for cost-efficient and spatially continuous measurements of beam losses at accelerator facilities. A standard oBLM consists of several tens of meters of optical fibre aligned parallel to the beamline, coupled to photosensors at either or both ends. Using the timing information from loss signals, the loss positions can be reconstructed. This contribution presents a novel oBLM system recently deployed at the CERN Linear Electron Accelerator for Research (CLEAR). Multiple methods of extracting timing and position information from measured waveforms are investigated, and the potential impact of varying beam parameters such as bunch charge or number is analysed. This work has resulted in the development of a GUI to aid operations by visualizing the beam losses and their positions in real time.

### Footnotes

### Funding Agency

### I have read and accept the Privacy Policy Statement

Yes

**Primary author:** KING, Montague (European Organization for Nuclear Research)

**Co-authors:** SALVACHUA, Belen (European Organization for Nuclear Research); Prof. WELSCH, Carsten (The University of Liverpool); EFFINGER, Ewald (European Organization for Nuclear Research); MEYER, Jean Michel (European Organization for Nuclear Research); WOLFENDEN, Joseph (Cockcroft Institute); KORYSKO, Pierre (Oxford University); BENITEZ, Sara (European Organization for Nuclear Research); FARABOLINI, Wilfrid (European Organization for Nuclear Research)

**Presenter:** KING, Montague (European Organization for Nuclear Research)

**Session Classification:** FRB: Beam Loss Monitors and Machine Protection/Beam Charge and Current Monitors

**Track Classification:** MC2: Beam Loss Monitors and Machine Protection