



Contribution ID: 69 Contribution code: TUP08

Type: **Poster Presentation**

## Design of button beam position monitor for the ILSF booster

*Tuesday 10 September 2024 16:00 (1h 30m)*

The Iranian Light Source Facility Booster is under design with a 504 m circumference and will accelerate the electron bunches from 150 MeV to 3 GeV. the 50 button-type beam position monitors (BPMs) are considered the non-destructive tools to measure the beam position in the ILSF booster. In this paper, the design of the BPM for the ILSF booster is studied. The BPM blocks have 4 buttons (electrodes) that are placed at 45 degrees to the beam axis. to choose the best geometry, The BPMs with different button diameters and gaps are simulated by the CST Microwave Studio and BpmLab.

### Footnotes

### Funding Agency

### I have read and accept the Privacy Policy Statement

Yes

**Primary author:** MOHAMMADI ALAMOUTI, Samira (Iranian Light Source Facility)

**Co-authors:** DANAEIFARD, Amir (Iranian Light Source Facility); KHOSRAVI, Nafiseh (Iranian Light Source Facility); REZAEI, Zahra (Iranian Light Source Facility)

**Presenter:** MOHAMMADI ALAMOUTI, Samira (Iranian Light Source Facility)

**Session Classification:** TUP: Tuesday Poster Session

**Track Classification:** MC3: Beam Position Monitors