



Contribution ID: 118

Type: **Poster Presentation**

Pulse Injection source for use with Cavity Beam Position Monitors

Tuesday, 10 September 2024 16:00 (1h 30m)

The Cavity Beam Position Monitor (CBPM) system at Accelerator Test Facility 2 (ATF2, KEK, Japan) operates with attenuation at a reduced 200 nm (vs measured 20-30 nm) resolution to cope with CBPM to magnet misalignment. In addition, CBPMs need regular calibrations to maintain their performance. To address these limitations, a pulse injection system is under development. This system aims to compensate for static offsets by injecting an anti-phase replica of the average beam signal directly into the sensor cavities. The same signal can provide a calibration tone for the whole processing chain and eliminate lengthy beam-based calibrations. Proof of principle tests for such a system have been conducted in December 2023. In this paper, we report on the results of the first beam test, discuss the technical challenges and provide a preliminary hardware specification for future experiments.

Footnotes

Funding Agency

I have read and accept the Privacy Policy Statement

Yes

Primary author: MCCALLUM, Mark (John Adams Institute)

Co-authors: ARYSHEV, Alexander (High Energy Accelerator Research Organization); LYAPIN, Alexey (John Adams Institute); Dr POPOV, Konstantin (High Energy Accelerator Research Organization (KEK)); TERUNUMA, Nobuhiro (High Energy Accelerator Research Organization)

Presenter: MCCALLUM, Mark (John Adams Institute)

Session Classification: TUP: Tuesday Poster Session

Track Classification: MC3: Beam Position Monitors