



Contribution ID: 186

Type: **Poster Presentation**

Wide range and high precision grid-cathode modulation of beam current for High Energy Photon Source electron gun

Thursday, 12 September 2024 16:00 (1h 30m)

High Energy Photon Source (HEPS) is the fourth-generation light source under construction in China. The electron gun system is the origin of beam acceleration. This article introduces the wide range and high precision grid-cathode modulation of beam current for the HEPS electron gun system. Its grid-bias voltage adjustment is as fine as 0.01V. Cathode filament current and voltage ripple $< 0.1\%$. Its grid-bias voltage adjustment accuracy reaches 0.01V. The cathode filament current and voltage ripple $< 0.1\%$. The beam test results show that the beam current amplitude stabilization of 2.37% (small current), 0.13% (high current), beam current time jitter 12.459ps. Meets physical requirements for a wide range of injector from 2.8nC to 7nC.

Footnotes

Funding Agency

This work was supported by National Natural Science Foundation of China (Grant No. 12205320, Grant No.12275288)

I have read and accept the Privacy Policy Statement

Yes

Primary author: LIU, Jingdong (Chinese Academy of Sciences)

Co-authors: HE, Dayong (Institute of High Energy Physics); LI, Jingyi (Institute of High Energy Physics); ZHOU, Zusheng (Institute of High Energy Physics); HE, Xiang (Chinese Academy of Sciences); Dr MENG, Cai (Chinese Academy of Sciences); LI, Xiaoping (Chinese Academy of Sciences); ZHANG, Jingru (Chinese Academy of Sciences)

Presenter: LIU, Jingdong (Chinese Academy of Sciences)

Session Classification: THP: Thursday Poster Session

Track Classification: MC1: Beam Charge and Current Monitors