



Contribution ID: 200

Type: **Poster Presentation**

## Measurement of beam energy characteristics at the LHe-free Nb<sub>3</sub>Sn demo SRF e-linac

Thursday, 12 September 2024 16:00 (1h 30m)

The demonstration of a 100mA, 4.6MeV superconducting radio frequency linear electron accelerator, based on conduction cooling and developed by the Institute of Modern Physics (IMP), aims to validate the feasibility of stable beam commissioning in a liquid helium-free 5-cell- $\beta_{opt}=0.82$  Nb<sub>3</sub>Sn elliptical cavity, and to offer guidance for subsequent industrial applications. The beam energy characteristics, considered one of the critical parameters, need to be precisely measured. Due to the high energy of the beam and the compact, simple layout requirement of this accelerator, only one dipole magnet is used for energy measurement. This paper compares errors from three different experimental processes, presenting simulation and online measurement results of energy measurement under various cavity voltage. It analyzes the impact of various errors during online energy measurement and examines the effects of the slit after the dipole and its shape on energy measurement.

### Footnotes

### Funding Agency

### I have read and accept the Privacy Policy Statement

Yes

**Primary author:** CHU, Yimeng (Institute of Modern Physics, Chinese Academy of Sciences)

**Co-authors:** WANG, Zhijun (Institute of Modern Physics, Chinese Academy of Sciences); CHEN, Weilong (Institute of Modern Physics, Chinese Academy of Sciences); LIANG, Zehua (Institute of Modern Physics, Chinese Academy of Sciences); WANG, tielong (Institute of Modern physics, Chinese Academy of Science); JIA, Duanyang (Institute of Modern Physics, Chinese Academy of Sciences)

**Presenter:** CHU, Yimeng (Institute of Modern Physics, Chinese Academy of Sciences)

**Session Classification:** THP: Thursday Poster Session

**Track Classification:** MC8: Machine Parameter Measurements