



Contribution ID: 150 Contribution code: THP52

Type: Poster Presentation

Development status of the fiber length stabilizers for the laser arrival-time measurement

Thursday 12 September 2024 16:00 (1h 30m)

The Shanghai soft X-ray Free-Electron Laser facility (SXFEL) is a fourth-generation linac-based light source, capable of producing X-ray pulses with duration of tens of femtosecond. The photocathode laser and the seed laser for external seeding FEL therefore have tight requirements for relative arrival time to the machine and electron bunch. To reach required energy and wavelength to drive photocathode, as well as for external seeding FEL, further optical amplification and frequency conversion is needed. the femtosecond-stable pulsed optical reference, which are delivered via fiber length stabilizers. In this paper, we present the development status of the fiber length stabilizers for the laser-arrival time measurement.

Footnotes

Funding Agency

I have read and accept the Privacy Policy Statement

Yes

Primary author: WU, Bowei (Shanghai Advanced Research Institute)

Co-authors: LIU, Bo (Shanghai Advanced Research Institute); WANG, Jinguo (Shanghai Advanced Research Institute)

Presenter: WU, Bowei (Shanghai Advanced Research Institute)

Session Classification: THP: Thursday Poster Session

Track Classification: MC5: Longitudinal Diagnostics and Synchronization