



Contribution ID: 88 Contribution code: THP42

Type: Poster Presentation

A test bench for 324MHz RF deflectors used in bunch shape monitors for the upgrade of CSNS-II linac

Thursday, 12 September 2024 16:00 (1h 30m)

The Feschenko-type bunch shape monitors based on the transverse modulation of low energy secondary emission electrons, will be used in the measurement of longitudinal beam density distribution in the upgrade of CSNS-II linac. A test bench for commissioning the 324MHz RF deflectors used in BSM has been built in the laboratory, which consists of a Kimball E-gun, an RF stimulator, a 324MHz RF power source and a set of MCP+Screen. This paper gives the design consideration, test results of the test bench and the continuing CST design of a $\lambda/2$ RF deflector.

Footnotes

Funding Agency

Work supported by Natural Science Foundation 12275294, and Mega Science Project Operation Fund of CSNS

I have read and accept the Privacy Policy Statement

Yes

Primary authors: LIU, Quanru (University of Chinese Academy of Sciences); HUANG, Weiling (Institute of High Energy Physics)

Co-authors: LI, Fang (Institute of High Energy Physics); ZENG, Lei (Institute of High Energy Physics); LIU, Mengyu (Chinese Academy of Sciences); REHMAN, Muhammad Abdul (Institute of High Energy Physics); YANG, Renjun (Institute of High Energy Physics); QIU, Ruiyang (Institute of High Energy Physics); YANG, Tao (Institute of High Energy Physics); NIE, Xiaojun (Institute of High Energy Physics); XU, Zhihong (Institute of High Energy Physics)

Presenters: LIU, Quanru (University of Chinese Academy of Sciences); HUANG, Weiling (Institute of High Energy Physics)

Session Classification: THP: Thursday Poster Session

Track Classification: MC5: Longitudinal Diagnostics and Synchronization