



Contribution ID: 1056 Contribution code: MOPS105

Type: **Poster Presentation**

## Optimizations for enhancing performance of emittance exchange-based photoinjector

*Monday 2 June 2025 16:00 (2 hours)*

A recent simulation study demonstrated the potential to achieve high 4D-emittance using an emittance exchange (EEX) beamline integrated within a photoinjector. This EEX beamline enabled to achieve the final normalized longitudinal emittance of 0.44 micron, which corresponds to rms bunch length of 7micron and energy spread of 32keV. These results are noteworthy for a 60-MeV photoinjector comprising a gun, linac, and EEX beamline. However, the transverse emittance of approximately 0.6 micron remains a limitation for many applications. To address this, we have conducted computational studies to improve the performance of EEX photoinjector. We present the progress achieved thus far.

### Footnotes

### Paper preparation format

Others

### Region represented

Asia

### Funding Agency

**Author:** SEO, MinKyu (Korea University Sejong Campus)

**Co-authors:** HA, Gwanghui (Northern Illinois University); PARK, Seong Hee (Korea University Sejong Campus)

**Presenter:** SEO, MinKyu (Korea University Sejong Campus)

**Session Classification:** Monday Poster Session

**Track Classification:** MC1 :Colliders and Related Accelerators: MC1.A08 Linear Accelerators