



Contribution ID: 2069 Contribution code: WEPB017

Type: **Poster Presentation**

Identifying the connections between grain growth and flux expulsion in low RRR niobium SRF cavities

Wednesday 4 June 2025 16:00 (2 hours)

The SRF community has shown that high temperature annealing can improve the flux expulsion of niobium cavities during cooldown. The required temperature will vary between cavities and different batches of material, typically around 800 C and up to 1000 C. However, for niobium with a low residual resistance ratio (RRR), even 1000 C is not enough to improve its poor flux expulsion. The purpose of this study is to observe the grain growth behavior of low RRR niobium coupons subjected to high temperature annealing to identify the mechanism for improving flux expulsion. We observe that low RRR material experiences less grain growth than high RRR when annealed at the same temperature. We search for the limitations to grain growth in low RRR material and develop a diagnostic based on grain structure to determine the appropriate recipe for good flux expulsion. The results of this study have the potential to unlock a new understanding on SRF materials and enable the next generation of high Q/high gradient surface treatments.

Footnotes

Paper preparation format

LaTeX

Region represented

America

Funding Agency

This manuscript has been authored by Fermi Research Alliance, LLC under Contract No. DE-AC02-07CH11359 with the U.S. Department of Energy, Office of Science, Office of High Energy Physics.

Author: HOWARD, Katrina (University of Chicago)

Co-authors: BAFIA, Daniel (Fermi National Accelerator Laboratory); SUNG, Zu-Hawn (Fermi National Accelerator Laboratory); DZIEDZIC-MISIEWICZ, Wieslawa (Fermi National Accelerator Laboratory); KIM, Young-Kee (University of Chicago)

Presenter: HOWARD, Katrina (University of Chicago)

Session Classification: Wednesday Poster Session

Track Classification: MC7: Accelerator Technology and Sustainability: MC7.T07 Superconducting

RF