

Contribution ID: 2281

**Type: Poster Presentation** 

# Design and cold test of a high-efficiency C-band travelling-wave accelerating structure

In this paper we present the development of a 1-meter high-efficiency C-band travelling wave (TW) accelerating structure for the proposed Jinhua Light Source (JHLS) project including the design and cold test. This C-band structure works at a mode of  $3\pi/4$  with a relatively low group velocity varying from 0.016c to 0.009c. It employs a cell shape with elliptical irises and circular arc tops to reduce the surface electric and magnetic fields and to achieve an average shunt impedance of 94 M $\Omega$ /m through optimizations. This results in an accelerating gradient of 40 MV/m with an input power of 29.6 MW, which has an efficiency comparatively higher than those of previously-reported C-band structures. Moreover, a new technique is utilized for the design of couplers, significantly simplifying the whole optimization process and achieves high accuracy. After fabrication, the structure was precisely tuned. Results from low-power radiofrequency (RF) measurements and the comparison with simulated values are also presented in this paper.

#### **Footnotes**

## Paper preparation format

Word

#### Region represented

Asia

### **Funding Agency**

Author: ZHANG, Yihao (University of Science and Technology of China)

**Co-authors:** WANG, Chengzhe (University of Science and Technology of China); ALESINI, David (Istituto Nazionale di Fisica Nucleare); FENG, Guangyao (University of Science and Technology of China); SUN, Li (University of Science and Technology of China); FAILLACE, Luigi (Istituto Nazionale di Fisica Nucleare); WEI, Yelong (University of Science and Technology of China); CAO, Zexin (University of Science and Technology of China); HUANG, Zhicheng (University of Science and Technology of China)

Presenter: WANG, Chengzhe (University of Science and Technology of China)

Session Classification: Student Training

Track Classification: MC7: Accelerator Technology and Sustainability: MC7.T06 Normal Conducting

RF