



Identifying the connections between grain growth and flux expulsion in low RRR niobium SRF cavities

Tuesday 23 September 2025 14:30 (3 hours)

The SRF community has shown that high temperature annealing can improve the flux expulsion of niobium cavities during cooldown. The required temperature will vary between cavities and different batches of material, typically around 800 C and up to 1000 C. However, for niobium with a low residual resistance ratio (RRR), even 1000 C is not enough to improve its poor flux expulsion. The purpose of this study is to observe the grain growth behavior of low RRR niobium coupons subjected to high temperature annealing to identify the mechanism for improving flux expulsion. We observe that low RRR material experiences less grain growth than high RRR when annealed at the same temperature. We search for the limitations to grain growth in low RRR material and develop a diagnostic based on grain structure to determine the appropriate recipe for good flux expulsion. The results of this study have the potential to unlock a new understanding on SRF materials and enable the next generation of high Q/high gradient surface treatments.

I have read and accept the Privacy Policy Statement

Yes

Footnotes

Funding Agency

Work supported by the Fermi National Accelerator Laboratory, managed and operated by Fermi Forward Discovery Group, LLC under Contract No. 89243024CSC000002 with the U.S. Department of Energy.

Author: HOWARD, Katrina (University of Chicago)

Co-authors: BAFIA, Daniel (Fermi National Accelerator Laboratory); SUNG, Zuhawn (Fermi National Accelerator Laboratory); DZIEDZIC-MISIEWICZ, Wieslawa (Fermi National Accelerator Laboratory); KIM, Young-Kee (University of Chicago; Fermi National Accelerator Laboratory)

Presenter: HOWARD, Katrina (University of Chicago)

Session Classification: Tuesday Poster Session

Track Classification: MC2: Fundamental SRF research and development