



Contribution ID: 378

Type: **Poster Presentation**

Development of CMOS beam loss monitor for Korea-4GSR

Monday 8 September 2025 16:00 (2 hours)

The beam loss monitor (BLM) is a diagnostic system designed to protect accelerator components from unexpected high-energy radiation. We have developed a cost-effective BLM system for the next-generation synchrotron light source, Korea-4GSR.

The system uses plastic scintillators, optical fibers, and a CMOS camera to localize beam losses with 10 ms time resolution. Scintillators placed along the beam-line emit blue light proportional to the ionization energy deposited by beam losses. The light is transmitted through optical fibers, bundled into a 2D array, and imaged by a CMOS sensor at 100 Hz.

The BLM's sensitivity and calibration were verified using a 2 MBq Co-60 gamma-ray source. The preliminary result shows ~45 counts/GeV. Energy deposition was estimated using Geant4 simulations, and photon-to-count conversion was characterized with a calibrated LED source. The DAQ includes a built-in LED pulser for in-situ calibration of the CMOS detector and cable integrity check. This presentation outlines the system design, calibration methods, and performance results.

Footnotes

Funding Agency

The Korean Government MSIT (Multipurpose Synchrotron Radiation Construction Project) (RS-2022-00155836)

I have read and accept the Conference Policies

Yes

Authors: SHIN, Bokkyun (Pohang Accelerator Laboratory); KIM, Changbum (Pohang Accelerator Laboratory); Mr KIM, Do Tae (Pohang Accelerator Laboratory); SHIN, DongCheol (Pohang Accelerator Laboratory); SONG, Donghyun (Pohang Accelerator Laboratory); HAHN, Garam (Pohang Accelerator Laboratory); Mr KIM, Gyujin (Pohang Accelerator Laboratory); JANG, Si-Won (Pohang Accelerator Laboratory)

Presenter: SHIN, Bokkyun (Pohang Accelerator Laboratory)

Session Classification: MOP

Track Classification: MC02: Beam Loss Monitors and Machine Protection